

DIN rail bus connectors - ME 22,5 TBUS 1,5/ 5-ST-3,81 KM - 2713722


Please be informed that the data shown in this PDF Document is generated from our Online Catalog. Please find the complete data in the user's documentation. Our General Terms of Use for Downloads are valid (<http://phoenixcontact.com/download>)



DIN rail connector, number of positions: 5, pitch: 3.81 mm, color: light gray, Articles with gold-plated contacts, bus connectors for connecting with electronic housings

Your advantages

- ✓ Space-saving DIN rail mounting
- ✓ Contact design enables electronics modules to be easily snapped on
- ✓ Power supply and communication without additional wiring
- ✓ Parallel and serial contacts for signal and data transmission



Key Commercial Data

Packing unit	1 pc
GTIN	 4 017918 914516
GTIN	4017918914516
Weight per Piece (excluding packing)	5.200 g
Custom tariff number	85366990
Country of origin	Germany

Technical data

Dimensions

Width	22.5 mm
Pitch	3.81 mm
Width [w]	22.5 mm

General

Insulating material group	I
---------------------------	---

DIN rail bus connectors - ME 22,5 TBUS 1,5/ 5-ST-3,81 KM - 2713722

Technical data

General

Rated surge voltage (III/3)	2.5 kV
Rated surge voltage (III/2)	2.5 kV
Rated surge voltage (II/2)	1.5 kV
Rated voltage (III/3)	125 V
Rated voltage (III/2)	100 V
Rated voltage (II/2)	150 V
Nominal current I _N	8 A
Maximum load current	8 A
Insulating material	PA
Flammability rating according to UL 94	V0
Color	light gray
Number of positions	5

General product information

Type of note	Recommendation
Note	Material of contact pads for bus connector, galvanic gold (hard gold)

Standards and Regulations

Connection in acc. with standard	CUL
Flammability rating according to UL 94	V0

Environmental Product Compliance

China RoHS	Environmentally friendly use period: unlimited = EFUP-e
	No hazardous substances above threshold values

Classifications

eCl@ss

eCl@ss 4.0	27260700
eCl@ss 4.1	27260700
eCl@ss 5.0	27260700
eCl@ss 5.1	27260700
eCl@ss 6.0	27260700
eCl@ss 7.0	27440309
eCl@ss 8.0	27440309
eCl@ss 9.0	27440309

ETIM

ETIM 2.0	EC001031
----------	----------

DIN rail bus connectors - ME 22,5 TBUS 1,5/ 5-ST-3,81 KM - 2713722

Classifications

ETIM

ETIM 3.0	EC001031
ETIM 4.0	EC002638
ETIM 5.0	EC002638
ETIM 6.0	EC002638
ETIM 7.0	EC002638

UNSPSC

UNSPSC 6.01	31261501
UNSPSC 7.0901	31261501
UNSPSC 11	31261501
UNSPSC 12.01	31261501
UNSPSC 13.2	39121409

Approvals

Approvals

Approvals

UL Recognized / cUL Recognized / EAC / cULus Recognized

Ex Approvals

Approval details

UL Recognized		http://database.ul.com/cgi-bin/XYV/template/LISEXT/1FRAME/index.htm	E118976-20151204
Nominal voltage UN	150 V		
Nominal current IN	8 A		

cUL Recognized		http://database.ul.com/cgi-bin/XYV/template/LISEXT/1FRAME/index.htm	E118976-20151204
Nominal voltage UN	150 V		
Nominal current IN	6 A		

DIN rail bus connectors - ME 22,5 TBUS 1,5/ 5-ST-3,81 KM - 2713722

Approvals

EAC



B.01742

cULus Recognized

