

Surge protection device - TT-UKK5-D/ 24DC - 2788090

Please be informed that the data shown in this PDF Document is generated from our Online Catalog. Please find the complete data in the user's documentation. Our General Terms of Use for Downloads are valid (<http://phoenixcontact.com/download>)



Double-level modular terminal block with suppressor diode as surge protection between both levels, nominal voltage: 24 V DC, for mounting on NS 32 or NS 35/7.5, closed housing, terminal width: 6.2 mm, terminal height: 68 mm



Key Commercial Data

Packing unit	1 pc
GTIN	 4 017918 071332
Weight per Piece (excluding packing)	24.504 g
Custom tariff number	85363010
Country of origin	Greece

Technical data

Dimensions

Height	68 mm
Width	6.2 mm
Length	80 mm

Ambient conditions

Ambient temperature (operation)	-40 °C ... 85 °C
Degree of protection	IP20

General

Housing material	PA
Flammability rating according to UL 94	V2
Color	black
Standards for clearances and creepage distances	VDE 0110-1
Mounting type	DIN rail/G-profile rail

Surge protection device - TT-UKK5-D/ 24DC - 2788090

Technical data

General

Type	Double-level terminal block
Direction of action	Line-Line

Protective circuit

IEC test classification	C3
VDE requirement class	C3
Nominal voltage U_N	24 V DC
Maximum continuous voltage U_C	28 V DC
	20 V AC
Maximum continuous voltage U_C (wire-wire)	28 V DC
	20 V AC
Nominal current I_N	16 A
Operating effective current I_C at U_C	$\leq 5 \mu A$
Nominal discharge current I_n (8/20) μs (Core-Core)	169 A
Total surge current (8/20) μs	169 A
Max. discharge current I_{max} (8/20) μs maximum (Core-Core)	169 A
Nominal pulse current I_{an} (10/1000) μs (Core-Core)	33 A
Output voltage limitation at 1 kV/ μs (Core-Core) static	$\leq 40 V$
Residual voltage at I_n (conductor-conductor)	$\leq 55 V$
Response time t_A (Core-Core)	$\leq 1 ns$
Cut-off frequency f_g (3 dB), sym. in 150 Ohm system	typ. 1.2 MHz
Capacity (Core-Core)	$\leq 1.6 nF$ (typical)
Impulse durability (conductor-conductor)	C3 - 25 A

Connection data

Connection method	Screw connection
Connection type IN	Screw terminal blocks
Connection type OUT	Screw terminal blocks
Screw thread	M3
Tightening torque	0.5 Nm
Stripping length	8 mm
Conductor cross section flexible min.	0.2 mm ²
Conductor cross section flexible max.	4 mm ²
Conductor cross section solid min.	0.2 mm ²
Conductor cross section solid max.	4 mm ²
Conductor cross section AWG min.	24
Conductor cross section AWG max.	12

Standards and Regulations

Surge protection device - TT-UKK5-D/ 24DC - 2788090

Technical data

Standards and Regulations

Standards/regulations	IEC 61643-21
-----------------------	--------------

Classifications

eCl@ss

eCl@ss 4.0	27140201
eCl@ss 4.1	27130801
eCl@ss 5.0	27130801
eCl@ss 5.1	27130801
eCl@ss 6.0	27130807
eCl@ss 7.0	27130807
eCl@ss 8.0	27130807
eCl@ss 9.0	27130807

ETIM

ETIM 2.0	EC000943
ETIM 3.0	EC000943
ETIM 4.0	EC000943
ETIM 5.0	EC000943

UNSPSC

UNSPSC 6.01	30212010
UNSPSC 7.0901	39121610
UNSPSC 11	39121610
UNSPSC 12.01	39121610
UNSPSC 13.2	39121620

Approvals

Approvals

Approvals

CSA / EAC / EAC

Ex Approvals

Surge protection device - TT-UKK5-D/ 24DC - 2788090

Approvals

Approvals submitted

Approval details


CSA 	
mm²/AWG/kcmil	24-12
Nominal current I _N	16 A
Nominal voltage U _N	24 V

EAC

EAC

Drawings

Circuit diagram



Surge protection device - TT-UKK5-D/ 24DC - 2788090

Schematic diagram

