

## Type 2 surge protection plug - VAL-MS 1000DC-PV-ST - 2800624

Please be informed that the data shown in this PDF Document is generated from our Online Catalog. Please find the complete data in the user's documentation. Our General Terms of Use for Downloads are valid (<http://phoenixcontact.com/download>)



Replacement plug for PV arrester combinations from the VAL-MS 1000DC-PV-... product range

RoHS

### Key Commercial Data

|                                      |                                                                                                         |
|--------------------------------------|---------------------------------------------------------------------------------------------------------|
| Packing unit                         | 1 pc                                                                                                    |
| GTIN                                 | <br>4 046356 615099 |
| GTIN                                 | 4046356615099                                                                                           |
| Weight per Piece (excluding packing) | 100.000 g                                                                                               |
| Custom tariff number                 | 85363010                                                                                                |
| Country of origin                    | Germany                                                                                                 |

### Technical data

#### Dimensions

|                  |         |
|------------------|---------|
| Height           | 52.4 mm |
| Width            | 17.5 mm |
| Depth            | 55.3 mm |
| Horizontal pitch | 1 Div.  |

#### Ambient conditions

|                                         |                                         |
|-----------------------------------------|-----------------------------------------|
| Degree of protection                    | IP20                                    |
| Ambient temperature (operation)         | -40 °C ... 80 °C                        |
| Ambient temperature (storage/transport) | -40 °C ... 80 °C                        |
| Altitude                                | ≤ 2000 m (amsl (above mean sea level))  |
| Permissible humidity (operation)        | 5 % ... 95 %                            |
| Shock (operation)                       | 60g (Half-sine / 11 ms / 3x ±X, ±Y, ±Z) |

# Type 2 surge protection plug - VAL-MS 1000DC-PV-ST - 2800624

## Technical data

### Ambient conditions

|                       |                           |
|-----------------------|---------------------------|
| Vibration (operation) | 7.5g (5-500 Hz/2.5 h/XYZ) |
|-----------------------|---------------------------|

### General

|                                                |                         |
|------------------------------------------------|-------------------------|
| IEC test classification                        | PV II                   |
|                                                | PV T2                   |
| EN type                                        | T2                      |
| SPD failure behavior                           | OCM (Open-circuit mode) |
| Installation location                          | Interior                |
| Accessibility                                  | Accessible              |
| Installation location of the disconnect device | Internal                |
| Mounting type                                  | on base element         |
| Color                                          | jet black RAL 9005      |
| Housing material                               | PA 6.6-FR               |
| Degree of pollution                            | 2                       |
| Flammability rating according to UL 94         | V-0                     |
| Type                                           | Male                    |
| Surge protection fault message                 | optical                 |

### Protective circuit DC voltage side (DC)

|                                                    |                              |
|----------------------------------------------------|------------------------------|
| Maximum continuous operating voltage $U_{CPV}$     | 585 V DC                     |
| Short-circuit current rating $I_{SCP}$             | 2000 A                       |
| Continuous operating current $I_{CPV}$             | < 20 $\mu$ A                 |
| Standby power consumption $P_C$                    | $\leq$ 25 mVA                |
| Nominal discharge current (8/20) $\mu$ s           | 15 kA                        |
| Maximum discharge current $I_{max}$ (8/20) $\mu$ s | 40 kA                        |
| Voltage protection level $U_p$                     | $\leq$ 1.9 kV                |
| Residual voltage $U_{res}$                         | $\leq$ 1.9 kV (at $I_n$ )    |
|                                                    | $\leq$ 1.5 kV (at 5 kA)      |
|                                                    | $\leq$ 1.7 kV (at 10 kA)     |
|                                                    | $\leq$ 2 kV (at 20 kA)       |
|                                                    | $\leq$ 2.3 kV (at 30 kA)     |
|                                                    | $\leq$ 2.5 kV (at 40 kA)     |
| Response time $t_A$                                | $\leq$ 25 ns                 |
| Insulation resistance $R_{iso}$                    | > 5 G $\Omega$ (at 500 V DC) |

### Connection data

|                   |           |
|-------------------|-----------|
| Connection method | pluggable |
|-------------------|-----------|

### UL specifications

## Type 2 surge protection plug - VAL-MS 1000DC-PV-ST - 2800624

### Technical data

#### UL specifications

|                                           |             |
|-------------------------------------------|-------------|
| SPD Type                                  | 1CA         |
| Maximum continuous operating voltage MCOV | 1170 V DC   |
| Nominal voltage                           | 1170 V DC   |
| Mode of protection                        | (L+) - (L-) |
|                                           | (L+) - G    |
|                                           | (L-) - G    |
| Power distribution system                 | DC PV       |
| Voltage protection rating VPR             | 3 kV        |
| Nominal discharge current $I_n$           | 10 kA       |
| Short-circuit current rating (SCCR)       | 50 kA       |

#### Standards and Regulations

|                       |                  |
|-----------------------|------------------|
| Standards/regulations | EN 50539-11 2013 |
|-----------------------|------------------|

#### Environmental Product Compliance

|            |                                                         |
|------------|---------------------------------------------------------|
| China RoHS | Environmentally friendly use period: unlimited = EFUP-e |
|            | No hazardous substances above threshold values          |

### Drawings


## Type 2 surge protection plug - VAL-MS 1000DC-PV-ST - 2800624

Circuit diagram



## Type 2 surge protection plug - VAL-MS 1000DC-PV-ST - 2800624

Dimensional drawing



### Classifications

#### eCl@ss

|               |          |
|---------------|----------|
| eCl@ss 10.0.1 | 27130890 |
| eCl@ss 4.0    | 27130800 |
| eCl@ss 4.1    | 27130800 |
| eCl@ss 5.0    | 27130800 |
| eCl@ss 5.1    | 27130800 |
| eCl@ss 6.0    | 27130800 |
| eCl@ss 7.0    | 27130805 |
| eCl@ss 8.0    | 27130890 |
| eCl@ss 9.0    | 27130890 |

#### ETIM

|          |          |
|----------|----------|
| ETIM 3.0 | EC000941 |
| ETIM 4.0 | EC000941 |
| ETIM 5.0 | EC002496 |
| ETIM 6.0 | EC000941 |
| ETIM 7.0 | EC000941 |

#### UNSPSC

|               |          |
|---------------|----------|
| UNSPSC 6.01   | 30212010 |
| UNSPSC 7.0901 | 39121610 |

## Type 2 surge protection plug - VAL-MS 1000DC-PV-ST - 2800624

### Classifications

#### UNSPSC

|              |          |
|--------------|----------|
| UNSPSC 11    | 39121610 |
| UNSPSC 12.01 | 39121610 |
| UNSPSC 13.2  | 39121620 |
| UNSPSC 18.0  | 39121620 |
| UNSPSC 19.0  | 39121620 |
| UNSPSC 20.0  | 39121620 |
| UNSPSC 21.0  | 39121620 |

### Approvals

#### Approvals

#### Approvals

UL Recognized / KEMA-KEUR / cUL Recognized / EAC / cULus Recognized

#### Ex Approvals

#### Approval details

|               |                                                                                     |                                                                                                                                                       |               |
|---------------|-------------------------------------------------------------------------------------|-------------------------------------------------------------------------------------------------------------------------------------------------------|---------------|
| UL Recognized |  | <a href="http://database.ul.com/cgi-bin/XYV/template/LISEXT/1FRAME/index.htm">http://database.ul.com/cgi-bin/XYV/template/LISEXT/1FRAME/index.htm</a> | FILE E 330181 |
|---------------|-------------------------------------------------------------------------------------|-------------------------------------------------------------------------------------------------------------------------------------------------------|---------------|

|           |                                                                                     |                                                                                     |           |
|-----------|-------------------------------------------------------------------------------------|-------------------------------------------------------------------------------------|-----------|
| KEMA-KEUR |  | <a href="http://www.dekra-certification.com">http://www.dekra-certification.com</a> | 71-102960 |
|-----------|-------------------------------------------------------------------------------------|-------------------------------------------------------------------------------------|-----------|

|                |                                                                                     |                                                                                                                                                       |               |
|----------------|-------------------------------------------------------------------------------------|-------------------------------------------------------------------------------------------------------------------------------------------------------|---------------|
| cUL Recognized |  | <a href="http://database.ul.com/cgi-bin/XYV/template/LISEXT/1FRAME/index.htm">http://database.ul.com/cgi-bin/XYV/template/LISEXT/1FRAME/index.htm</a> | FILE E 330181 |
|----------------|-------------------------------------------------------------------------------------|-------------------------------------------------------------------------------------------------------------------------------------------------------|---------------|

|     |                                                                                     |  |                         |
|-----|-------------------------------------------------------------------------------------|--|-------------------------|
| EAC |  |  | RU C-<br>DE.A*30.B01561 |
|-----|-------------------------------------------------------------------------------------|--|-------------------------|

## Type 2 surge protection plug - VAL-MS 1000DC-PV-ST - 2800624

### Approvals

cULus Recognized



### Accessories

#### Accessories

#### Device marking

Zack marker strip - ZBN 18:UNBEDRUCKT - 2809128



Zack marker strip, Strip, white, unlabeled, can be labeled with: CMS-P1-PLOTTER, PLOTMARK, mounting type: snap into tall marker groove, for terminal block width: 18 mm, lettering field size: 18 x 5 mm, Number of individual labels: 5

#### Labeled device marker

Marker for terminal blocks - ZBN 18,LGS:ERDE - 2749589



Marker for terminal blocks, Strip, white, labeled, horizontal: Grounding symbol, mounting type: snap into tall marker groove, for terminal block width: 18 mm, lettering field size: 18 x 5 mm, Number of individual labels: 5

Marker for terminal blocks - ZBN 18,LGS:L1-N,ERDE - 2749576



Marker for terminal blocks, Strip, white, labeled, horizontal: L1, L2, L3, N, GND, mounting type: snap into tall marker groove, for terminal block width: 18 mm, lettering field size: 18 x 5 mm, Number of individual labels: 5

#### Marker pen

## Type 2 surge protection plug - VAL-MS 1000DC-PV-ST - 2800624

### Accessories

Marker pen - B-STIFT - 1051993



Marker pen, for manual labeling of unprinted Zack strips, smear-proof and waterproof, line thickness 0.5 mm