

Remote bus cable - IBS RBC METER-T - 2806286

Please be informed that the data shown in this PDF Document is generated from our Online Catalog. Please find the complete data in the user's documentation. Our General Terms of Use for Downloads are valid (<http://phoenixcontact.com/download>)



Remote bus cable for fixed installation, sold by the meter

The illustration shows the versions standard, highly flexible and remote bus cables for underground runs

Key Commercial Data

Packing unit	1 M
GTIN	 4 017918 074791
Weight per Piece (excluding packing)	70.16 g
Custom tariff number	85444993
Country of origin	Germany

Technical data

Ambient conditions

Ambient temperature (operation)	-30 °C ... 70 °C
	-30 °C ... 70 °C
Ambient temperature (storage/transport)	-30 °C ... 70 °C

External sheath

Outer sheath, material	Special mixture on PVC base
External sheath, color	green RAL 6017
External diameter	7.2 mm

Single wire

Individual wires per module	6
Single wire, color	Color-coded DIN 47100
Single wire, material	Bare Cu litz wire
Single wire, cross section	0.22 mm ²
Structural data	7-strand Litz wires

Remote bus cable - IBS RBC METER-T - 2806286

Technical data

Mechanical properties

Smallest bending radius, fixed installation	8 x 7.2 mm
---	------------

General

Number of positions	6
---------------------	---

Classifications

eCl@ss

eCl@ss 4.0	27250281
eCl@ss 4.1	27250281
eCl@ss 5.0	27061801
eCl@ss 5.1	27061801
eCl@ss 6.0	27061801
eCl@ss 7.0	27061801
eCl@ss 8.0	27061801
eCl@ss 9.0	27061801

ETIM

ETIM 2.0	EC000304
ETIM 3.0	EC000830
ETIM 4.0	EC000830
ETIM 5.0	EC000830

UNSPSC

UNSPSC 6.01	43172015
UNSPSC 7.0901	43201404
UNSPSC 11	39121311
UNSPSC 12.01	39121311
UNSPSC 13.2	39121311

Approvals

Approvals

Approvals

INTERBUS CLUB / EAC

Remote bus cable - IBS RBC METER-T - 2806286

Approvals

Ex Approvals

Approvals submitted

Approval details

INTERBUS CLUB

EAC
