

Surge protection plug - PT 4- 5DC-ST - 2839211

Please be informed that the data shown in this PDF Document is generated from our Online Catalog. Please find the complete data in the user's documentation. Our General Terms of Use for Downloads are valid (<http://phoenixcontact.com/download>)



Protective plug PT with protective circuit for a 4-core floating signal circuit. Nominal voltage: 5 V DC

Product Features

- Plugs can be checked with CHECKMASTER
- Maximum ease of maintenance thanks to the two-piece design
- Base element remains an integral part of the installation
- Consistent plug-in signal circuit protection
- Impedance-neutral disconnection of plug for test and maintenance purposes



Key Commercial Data

Packing unit	1 pc
Weight per Piece (excluding packing)	24.84 g
Custom tariff number	85363010
Country of origin	Germany

Technical data

Dimensions

Height	45 mm
Width	17.7 mm
Depth	52 mm
Horizontal pitch	1 Div.
Complete module height	90 mm
Complete module width	17.7 mm
Complete module depth	65.5 mm

Surge protection plug - PT 4- 5DC-ST - 2839211

Technical data

Ambient conditions

Ambient temperature (operation)	-40 °C ... 85 °C
Degree of protection	IP20

General

Housing material	PA 6.6
Flammability rating according to UL 94	V0
Color	black
Standards for clearances and creepage distances	VDE 0110-1
	IEC 60664-1
Mounting type	On base element
Type	DIN rail module, two-section, divisible
Direction of action	Line-Line & Line-Signal Ground/Shield & optional Signal Ground/Shield-Earth Ground
Arrester can be tested with CHECKMASTER from software version:	From SW rev. 1.00

Protective circuit

IEC test classification	C1
	C2
	C3
	D1
VDE requirement class	C1
	C2
	C3
	D1
Nominal voltage U_N	5 V DC
Maximum continuous voltage U_C	6 V DC
	4 V AC
Maximum continuous voltage U_C (wire-wire)	6 V DC
	4 V AC
Nominal current I_N	2 A (80 °C)
Operating effective current I_C at U_C	$\leq 300 \mu A$
Residual current I_{PE}	$\leq 4 \mu A$ (Directly grounded)
	$\leq 1 \mu A$ (BE: 4+F)
Nominal discharge current I_n (8/20) μs (Core-Core)	720 A
Nominal discharge current I_n (8/20) μs (Core-Earth)	10 kA
Total surge current (8/20) μs	20 kA
Max. discharge current I_{max} (8/20) μs maximum (Core-Core)	720 A
Max. discharge current I_{max} (8/20) μs maximum (Core-Earth)	10 kA

Surge protection plug - PT 4- 5DC-ST - 2839211

Technical data

Protective circuit

Nominal pulse current I_{an} (10/1000) μ s (Core-Core)	160 A
Impulse discharge current (10/350) μ s, peak value I_{imp}	2.5 kA (per path)
Output voltage limitation at 1 kV/ μ s (Core-Core) spike	≤ 13 V
Output voltage limitation at 1 kV/ μ s (Core-Earth) spike	≤ 450 V
	≤ 1 kV (BE: 4+F)
Output voltage limitation at 1 kV/ μ s (Core-Core) static	≤ 10 V
Residual voltage at I_n (conductor-conductor)	≤ 40 V
Residual voltage with I_{an} (10/1000) μ s (conductor-conductor)	≤ 20 V
Voltage protection level U_p (core-core)	≤ 30 V (C1 (1 kV/500 A))
Voltage protection level U_p (core-ground)	≤ 450 V
	≤ 1 kV (BE: 4+F)
Response time t_A (Core-Core)	≤ 1 ns
Response time t_A (Core-Earth)	≤ 1 ns
	≤ 100 ns
Input attenuation aE, sym.	0.1 dB (≤ 250 kHz)
Cut-off frequency f_g (3 dB), sym. in 50 Ohm system	typ. 1 MHz
Surge protection fault message	None
Max. required back-up fuse	2 A (e.g. T (IEC 127-2/III))
Impulse durability (conductor-conductor)	C1 - 1 kV/500 A
	C3 - 100 A
Impulse durability (conductor-ground)	C2 - 10 kV/5 kA
	D1 - 2.5 kA

Connection data

Connection method	Screw connection (in connection with the base element)
Connection type IN	PLUGTRAB plug-in system
Connection type OUT	PLUGTRAB plug-in system
Screw thread	M3
Tightening torque	0.5 Nm
Stripping length	8 mm
Conductor cross section flexible min.	0.2 mm ²
Conductor cross section flexible max.	2.5 mm ²
Conductor cross section solid min.	0.2 mm ²
Conductor cross section solid max.	4 mm ²
Conductor cross section AWG min.	24
Conductor cross section AWG max.	12

Standards and Regulations

Surge protection plug - PT 4- 5DC-ST - 2839211

Technical data

Standards and Regulations

Standards/regulations	IEC 61643-21
	DIN EN 61643-21
	UL 497B

Classifications

eCl@ss

eCl@ss 4.0	27140201
eCl@ss 4.1	27130801
eCl@ss 5.0	27130801
eCl@ss 5.1	27130801
eCl@ss 6.0	27130807
eCl@ss 7.0	27130807
eCl@ss 8.0	27130807
eCl@ss 9.0	27130807

ETIM

ETIM 2.0	EC000943
ETIM 3.0	EC000943
ETIM 4.0	EC000943
ETIM 5.0	EC000943

UNSPSC

UNSPSC 6.01	30212010
UNSPSC 7.0901	39121610
UNSPSC 11	39121610
UNSPSC 12.01	39121610
UNSPSC 13.2	39121620

Approvals

Approvals

Approvals

UL Listed / EAC / EAC

Surge protection plug - PT 4- 5DC-ST - 2839211

Approvals

Ex Approvals

UL Listed / cUL Listed / cULus Listed

Approvals submitted



Approval details

UL Listed 	
Nominal current IN	2 A
Nominal voltage UN	5 V

EAC

EAC

Drawings



The figure shows the complete module consisting of a base element and connector