

Antenna - RAD-ISM-900-ANT-OMNI-0-6 - 2867160

Please be informed that the data shown in this PDF Document is generated from our Online Catalog. Please find the complete data in the user's documentation. Our General Terms of Use for Downloads are valid (<http://phoenixcontact.com/download>)



Omnidirectional antenna, IP65 protection, cable length 2 m, connection MCX (male)

Product Features

- Small antennas are suitable for applications with a shorter range
- Large antennas are suitable for applications requiring longer range
- Point-to-multipoint configurations
- Mobile or stationary applications

Key Commercial Data

Packing unit	1 pc
Weight per Piece (excluding packing)	312.0 g
Custom tariff number	85177019
Country of origin	United States

Technical data

Dimensions

Width	0.3 cm
Height	8.9 cm

Ambient conditions

Degree of protection	IP65
Ambient temperature (operation)	-40 °C ... 75 °C

General

With connecting cable	yes
Frequency range	900 MHz
	900 MHz
Horizontal beamwidth	360 °
Vertical beamwidth	N/A
Impedance	50 Ω

Antenna - RAD-ISM-900-ANT-OMNI-0-6 - 2867160

Technical data

General

Gain	2.15 dBi
Connection method	MCX (male)

Classifications

eCl@ss

eCl@ss 4.0	27060805
eCl@ss 4.1	27060805
eCl@ss 5.0	27061805
eCl@ss 5.1	27061805
eCl@ss 6.0	27061805
eCl@ss 7.0	27061805
eCl@ss 8.0	19070105
eCl@ss 9.0	19070105

ETIM

ETIM 2.0	EC000416
ETIM 3.0	EC001698
ETIM 4.0	EC001698
ETIM 5.0	EC001698

UNSPSC

UNSPSC 6.01	43171611
UNSPSC 7.0901	43221706
UNSPSC 11	43171611
UNSPSC 12.01	43221706
UNSPSC 13.2	43221706