

Termination resistor - FL LCX 50-OHM - 2884978

Please be informed that the data shown in this PDF Document is generated from our Online Catalog. Please find the complete data in the user's documentation. Our General Terms of Use for Downloads are valid
(<http://phoenixcontact.com/download>)



A termination resistor must be screwed on at the end of the leaky wave conductor which does not contain any wireless part. It guarantees an antenna cable termination with the correct impedance and is important for every wireless installation.

RoHS

Key Commercial Data

Packing unit	1 STK
GTIN	 4 046356 173162
GTIN	4046356173162
Weight per Piece (excluding packing)	20.000 g
Custom tariff number	85366910
Country of origin	China

Technical data

General

Frequency range	2.4 GHz ... 6 GHz
Impedance	50 Ω
Connection method	N (male)

Environmental Product Compliance

China RoHS	Environmentally Friendly Use Period = 25;
	For details about hazardous substances go to tab "Downloads", Category "Manufacturer's declaration"

Termination resistor - FL LCX 50-OHM - 2884978

Classifications

eCl@ss

eCl@ss 4.0	27250313
eCl@ss 4.1	27250313
eCl@ss 5.0	19070403
eCl@ss 5.1	19070403
eCl@ss 6.0	19070490
eCl@ss 7.0	19070490
eCl@ss 8.0	19070403
eCl@ss 9.0	19070403

ETIM

ETIM 3.0	EC000448
ETIM 4.0	EC000448
ETIM 5.0	EC000448
ETIM 6.0	EC000448

UNSPSC

UNSPSC 6.01	20142601
UNSPSC 7.0901	20142601
UNSPSC 11	20142601
UNSPSC 12.01	20142601
UNSPSC 13.2	32121617