

## Cover - BC 71,6 DKL S TRANS - 2896128

Please be informed that the data shown in this PDF Document is generated from our Online Catalog. Please find the complete data in the user's documentation. Our General Terms of Use for Downloads are valid (http://phoenixcontact.com/download)



Installation component housing, Housing cover, Cross connection: Component housing, Color: transparent, Width: 71.6 mm

#### **Product Features**

- ☑ Conforms to DIN EN 43880
- ▼ Tool-free mounting
- Available in overall widths from one to nine width units (17.8 mm ... 161.6 mm)
- Inflammability class V0 according to UL 94
- ✓ Variety of connection technologies
- ☑ Can be mounted on the DIN rail or the wall
- Optional with bus connector for DIN rail mounting

## **Key Commercial Data**

Packing unit	1 pc
Minimum order quantity	10 pc
Weight per Piece (excluding packing)	18.0 g
Custom tariff number	85389099
Country of origin	Germany

#### Technical data

#### General

Housing type	Installation component housing
Housing material	Polyamide
Color	transparent

#### Ambient conditions

Ambient temperature (operation)	-40 °C 105 °C (depending on power dissipation)

#### **Dimensions**

1. m. m.	
Width	1 /1.6 mm
11120	



## Cover - BC 71,6 DKL S TRANS - 2896128

## Technical data

#### Technical data

Flammability rating according to UL 94	V0

## Classifications

### eCl@ss

eCl@ss 4.0	27180401
eCl@ss 4.1	27180401
eCl@ss 5.0	27180506
eCl@ss 5.1	27180506
eCl@ss 6.0	27180802
eCl@ss 7.0	27182702
eCl@ss 8.0	27182702

### **ETIM**

ETIM 2.0	EC001031
ETIM 3.0	EC001031
ETIM 4.0	EC000886
ETIM 5.0	EC001031

#### UNSPSC

UNSPSC 6.01	31261501
UNSPSC 7.0901	31261501
UNSPSC 11	31261501
UNSPSC 12.01	31261501
UNSPSC 13.2	31261501

## Approvals

#### Approvals

Approvals

UL Recognized / EAC

Ex Approvals

Approvals submitted



# Cover - BC 71,6 DKL S TRANS - 2896128

Δ	approvals
A	pproval details
l	JL Recognized <b>\$1</b>
E	EAC

Phoenix Contact 2015 @ - all rights reserved http://www.phoenixcontact.com