

Components of electronic housing - BC 107,6 DKL R KMGY - 2896173

Please be informed that the data shown in this PDF Document is generated from our Online Catalog. Please find the complete data in the user's documentation. Our General Terms of Use for Downloads are valid (http://phoenixcontact.com/download)



Installation component housing, Housing cover, Color: light gray, Width: 107.6 mm

Why buy this product

- Item is from the BC product range
- ☑ Conforms to DIN EN 43880
- ▼ Tool-free mounting
- Available in overall widths from one to nine width units (17.8 mm ... 161.6 mm)
- Inflammability class V0 according to UL 94
- Variety of connection technologies
- Optional with bus connector for DIN rail mounting

Key Commercial Data

Packing unit	1 STK
Minimum order quantity	10 STK
Weight per Piece (excluding packing)	13.220 g
Custom tariff number	85389099
Country of origin	Germany

Technical data

General

Housing type	Installation component housing
Housing material	Polycarbonate
Color	light gray

Ambient conditions

Ambient temperature (operation)	-40 °C 105 °C (depending on power dissipation)
Ambient temperature (operation)	-40 C 103 C (depending on power dissipation)

Dimensions

VAP 101	407.0
Width	1 107.6 mm



Components of electronic housing - BC 107,6 DKL R KMGY - 2896173

Technical data

Loch	กเกกไ	data
Techi	וווייםו	uaia

Flammability rating according to UL 94	V0	
Standards and Regulations		
Flammability rating according to UL 94	V0	
Environmental Product Compliance		
China RoHS	Environmentally friendly use period: unlimited = EFUP-e	
	No hazardous substances above threshold values	

Approvals

Approvals

Approvals

UL Recognized / EAC

Ex Approvals

Approval details

UL Recognized 1 http://database.ul.com/cgi-bin/XYV/template/LISEXT/1FRAME/index.htm FILE E 240868

EAC EAC-Zulassung

Phoenix Contact 2016 © - all rights reserved http://www.phoenixcontact.com