

Please be informed that the data shown in this PDF Document is generated from our Online Catalog. Please find the complete data in the user's documentation. Our General Terms of Use for Downloads are valid (http://phoenixcontact.com/download)

Installation component housing, Cover, width: 53.6 mm, color: light gray (7035)



Your advantages

- ☑ Conforms to DIN EN 43880
- ▼ Tool-free mounting
- Available in overall widths from one to nine width units (17.8 mm ... 161.6 mm)
- Inflammability class V0 according to UL 94
- Variety of connection technologies
- ☑ Can be mounted on the DIN rail or the wall



Key Commercial Data

| Packing unit | 1 pc |
|--------------------------------------|-----------------|
| Minimum order quantity | 10 pc |
| GTIN | 4 046356 103183 |
| GTIN | 4046356103183 |
| Weight per Piece (excluding packing) | 6.000 g |
| Custom tariff number | 85389099 |
| Country of origin | Germany |

Technical data

Item properties

| Brief article description | Housing cover |
|---------------------------|---------------|



Technical data

Item properties

| · | |
|----------------|----------------------------------|
| Туре | BC 53,6 DKL R KMGY |
| Order No. | 2896432 |
| Housing type | Installation component housing |
| Housing series | BC |
| Туре | Cover |
| Mounting type | Latching with upper housing part |

Dimensions

| Width [w] | 53.6 mm |
|--------------|---------|
| Height [h] | 45 mm |
| Depth [d] | 8 mm |

Material data

| Flammability rating according to UL 94 | V0 |
|--|---------------|
| Housing material | Polycarbonate |

Ambient conditions

| Ambient temperature (storage/transport) | -40 °C 70 °C |
|---|--|
| Ambient temperature (assembly) | -5 °C 100 °C |
| Ambient temperature (operation) | -40 °C 105 °C (depending on power dissipation) |

Packaging information

| Pieces per package | 10 |
|----------------------------|------|
| Denomination packing units | Pcs. |

Standards and regulations

| Flammability rating according to UL 94 | V0 |
|--|----|
|--|----|

Environmental Product Compliance

| China RoHS | Environmentally friendly use period: unlimited = EFUP-e |
|------------|---|
| | No hazardous substances above threshold values |

Classifications

eCl@ss

| eCl@ss 5.1 | 27180500 |
|------------|----------|
| eCl@ss 6.0 | 27180800 |
| eCl@ss 7.0 | 27182702 |
| eCl@ss 8.0 | 27182702 |
| eCl@ss 9.0 | 27182702 |



Classifications

ETIM

| ETIM 2.0 | EC001031 |
|----------|----------|
| ETIM 3.0 | EC001031 |
| ETIM 4.0 | EC000886 |
| ETIM 5.0 | EC001031 |
| ETIM 6.0 | EC001031 |
| ETIM 7.0 | EC001031 |

UNSPSC

| UNSPSC 6.01 | 31261501 |
|---------------|----------|
| UNSPSC 7.0901 | 31261501 |
| UNSPSC 11 | 31261501 |
| UNSPSC 12.01 | 31261501 |
| UNSPSC 13.2 | 31261501 |

Approvals

Approvals

Approvals

UL Recognized / EAC

Ex Approvals

Approval details

UL Recognized http://database.ul.com/cgi-bin/XYV/template/LISEXT/1FRAME/index.htm FILE E 240868

EAC B.01742

Accessories

Accessories

Fiber optic



Accessories

Fiber optic - HS LC-V-D3/ R2XC1-5,08 - 2202311



Light guides, passive, rigid, can be used for the BC housing range (housing must be processed)

Fiber optic - HS LC-V-D3/ R3XC1-5,08 - 2202312



Light guides, passive, rigid, can be used for the BC housing range (housing must be processed)

Phoenix Contact 2019 @ - all rights reserved <code>http://www.phoenixcontact.com</code>