

Antenna cable - PSI-CAB-GSM/UMTS- 5M - 2900980

Please be informed that the data shown in this PDF Document is generated from our Online Catalog. Please find the complete data in the user's documentation. Our General Terms of Use for Downloads are valid (<http://phoenixcontact.com/download>)

GSM/UMTS antenna cable, 5 m long; SMA (male) -> SMA (female), 50 Ohm impedance



Key Commercial Data

Packing unit	1 STK
Weight per Piece (excluding packing)	280.000 g
Custom tariff number	85442000
Country of origin	Poland

Technical data

Dimensions

Fixed cable length	5 m
External diameter	5.50 mm

Ambient conditions

Ambient temperature (operation)	-40 °C ... 85 °C
Ambient temperature (storage/transport)	-40 °C ... 85 °C

General

Connection 1	Connector connection
Connection method	SMA (male)
Connection 2	Connector connection
Connection method	SMA (female)
Outer sheath, material	LSFH
Minimum bending radius	82.00 mm
Frequency range	850 MHz
	900 MHz
	1800 MHz
	1900 MHz
	2100 MHz

Antenna cable - PSI-CAB-GSM/UMTS- 5M - 2900980

Technical data

General

Impedance	50 Ω
-----------	-------------

Attenuation

Cable, attenuation	Approx. 0.23 dB/m at 850 MHz
	Approximately 0.24 dB/m at 900 MHz
	Approximately 0.35 dB/m at 1.8 GHz
	Approximately 0.39 dB/m at 2.1 GHz

Environmental Product Compliance

China RoHS	Environmentally friendly use period: unlimited = EFUP-e
	No hazardous substances above threshold values

Approvals

Approvals

Approvals

EAC

Ex Approvals

Approval details

EAC EAC-Zulassung
