

Please be informed that the data shown in this PDF Document is generated from our Online Catalog. Please find the complete data in the user's documentation. Our General Terms of Use for Downloads are valid (http://phoenixcontact.com/download)



Software package for PC-based automation solutions, PC WORX BASIC license, contains all 5 IEC languages, without MSFC compiler, max. 2048 byte input and output data, version-specific license key

#### Your advantages

- Consistent support for drag-and-drop
- ☑ User-friendly device handling, thanks to integrated PROFINET, PROFIBUS, INTERBUS, and Modbus TCP configuration and addressing
- Program modifications can also be made while the controller is running
- Open interfaces to EPLAN, WinMOD, PLCopen XML
- ☑ Integrated simulation environment
- Integrated fieldbus and network configuration
- Application-specific expansion with corresponding functional blocks
- Integrated diagnostics and monitoring
- Fast startup and programming, thanks to comprehensive standard libraries
- Uniform operation worldwide, thanks to programming according to IEC 61131
- ☑ A programming environment for all controllers from Phoenix Contact



### **Key Commercial Data**

Packing unit	1 pc
GTIN	4 046356 099509
GTIN	4046356099509
Weight per Piece (excluding packing)	290.000 g
Custom tariff number	85234910
Country of origin	Germany



# Technical data

#### License information

Intended use for the software	Engineering software for controllers
Functions	

Basic functions	Planning an automation system, parameterizing the INTERBUS and PROFINET devices, operating INTERBUS and PROFINET, programming an automation system in acc. with IEC 61131-3. communication in acc. with IEC 61131-5
	Symbolic flowchart (SFC)
	Instruction list (IL)
	Structured text (ST)
	Ladder diagram (LD)
	Network configuration (functionality of Config+)
	Network diagnostics (functionality of Diag+)
Expanded functionality	2048 bytes of I/O data (mixed) (basic license)
Integrated function	Analysis
	Evaluation
	Data acquisition
	Programming
	Configuration
	Diagnostics
	Maintenance
	Communication
	Functional safety
Number of I/O nodes	2048 I/O bytes
Configuration	INTERBUS
	PROFINET
	Modbus/TCP
Diagnostics	INTERBUS
	PROFINET
Control system	(Target system) Embedded and PC-based controllers

## Hardware requirements

Hard disk	min. 2 GByte
RAM	min. 2 GByte
CPU	min. 2 GHz, x86 architecture
Interfaces	Serial COM port, Ethernet (PCI if there is an INTERBUS master card in the PC)
Optical drive	None
Monitor resolution	SXGA (1280 x 1024)



## Technical data

## Hardware requirements

Operating equipment	Keyboard, mouse

## Software requirements

Operating system	Windows® 7 Professional SP1 (32-Bit/64-Bit)
	Windows® 7 Ultimate SP1 (32-Bit/64-Bit)
	Windows <sup>®</sup> 8.1 Professional (32-Bit/64-Bit)
	Windows® 8.1 Enterprise (32-Bit/64-Bit)
	Windows® 10 (32-bit/64-bit), as of Build 1511
Languages supported	German, English, French, Italian, Spanish, Chinese

# Classifications

# eCl@ss

eCl@ss 5.1	27242500
eCl@ss 6.0	27242500
eCl@ss 7.0	27242501
eCl@ss 8.0	27242501
eCl@ss 9.0	27242501

### **ETIM**

ETIM 2.0	EC000809
ETIM 3.0	EC000809
ETIM 4.0	EC000809
ETIM 5.0	EC000809
ETIM 6.0	EC000809
ETIM 7.0	EC000809

## **UNSPSC**

UNSPSC 6.01	81111810
UNSPSC 7.0901	81111810
UNSPSC 11	81111810
UNSPSC 12.01	43232401
UNSPSC 13.2	43233603

#### Accessories

#### Accessories

Drivers and interfaces



#### Accessories

Software - AX OPC SERVER - 2985945



AX OPC SERVER, communication interface for OPC-capable visualization with PC WORX-based controls.

Phoenix Contact 2019 © - all rights reserved http://www.phoenixcontact.com