


## Feed-through terminal block - UK 5 BU - 3004090

Please be informed that the data shown in this PDF Document is generated from our Online Catalog. Please find the complete data in the user's documentation. Our General Terms of Use for Downloads are valid (<http://phoenixcontact.com/download>)



Feed-through terminal block, Connection method: Screw connection, Cross section: 0.2 mm<sup>2</sup> - 4 mm<sup>2</sup>, AWG: 24 - 10, Width: 6.2 mm, Color: blue, Mounting type: NS 35/7,5, NS 35/15, NS 32

### Key Commercial Data

|                                      |                                                                                                       |
|--------------------------------------|-------------------------------------------------------------------------------------------------------|
| Packing unit                         | 1 pc                                                                                                  |
| GTIN                                 | <br>4 017918 090616 |
| Weight per Piece (excluding packing) | 9.91 g                                                                                                |
| Custom tariff number                 | 85369010                                                                                              |
| Country of origin                    | Poland                                                                                                |

### Technical data

#### General

|                                        |       |
|----------------------------------------|-------|
| Number of levels                       | 1     |
| Number of connections                  | 2     |
| Color                                  | blue  |
| Insulating material                    | PA    |
| Flammability rating according to UL 94 | V0    |
| Rated surge voltage                    | 8 kV  |
| Degree of pollution                    | 3     |
| Overvoltage category                   | III   |
| Insulating material group              | I     |
| Nominal current I <sub>N</sub>         | 32 A  |
| Nominal voltage U <sub>N</sub>         | 800 V |
| Open side panel                        | Yes   |

#### Dimensions

|        |         |
|--------|---------|
| Width  | 6.2 mm  |
| Length | 42.5 mm |

# Feed-through terminal block - UK 5 BU - 3004090

## Technical data

### Dimensions

|                  |         |
|------------------|---------|
| Height NS 35/7,5 | 47 mm   |
| Height NS 35/15  | 54.5 mm |
| Height NS 32     | 52 mm   |

### Connection data

|                                                                                         |                      |
|-----------------------------------------------------------------------------------------|----------------------|
| Connection method                                                                       | Screw connection     |
| Conductor cross section solid min.                                                      | 0.2 mm <sup>2</sup>  |
| Conductor cross section solid max.                                                      | 4 mm <sup>2</sup>    |
| Conductor cross section AWG min.                                                        | 24                   |
| Conductor cross section AWG max.                                                        | 10                   |
| Conductor cross section flexible min.                                                   | 0.2 mm <sup>2</sup>  |
| Conductor cross section flexible max.                                                   | 4 mm <sup>2</sup>    |
| Min. AWG conductor cross section, flexible                                              | 24                   |
| Max. AWG conductor cross section, flexible                                              | 12                   |
| Conductor cross section flexible, with ferrule without plastic sleeve min.              | 0.25 mm <sup>2</sup> |
| Conductor cross section flexible, with ferrule without plastic sleeve max.              | 4 mm <sup>2</sup>    |
| Conductor cross section flexible, with ferrule with plastic sleeve min.                 | 0.25 mm <sup>2</sup> |
| Conductor cross section flexible, with ferrule with plastic sleeve max.                 | 2.5 mm <sup>2</sup>  |
| 2 conductors with same cross section, solid min.                                        | 0.2 mm <sup>2</sup>  |
| 2 conductors with same cross section, solid max.                                        | 1.5 mm <sup>2</sup>  |
| 2 conductors with same cross section, stranded min.                                     | 0.2 mm <sup>2</sup>  |
| 2 conductors with same cross section, stranded max.                                     | 1.5 mm <sup>2</sup>  |
| 2 conductors with same cross section, stranded, TWIN ferrules with plastic sleeve, min. | 0.5 mm <sup>2</sup>  |
| 2 conductors with same cross section, stranded, TWIN ferrules with plastic sleeve, max. | 2.5 mm <sup>2</sup>  |
| 2 conductors with same cross section, stranded, ferrules without plastic sleeve, min.   | 0.25 mm <sup>2</sup> |
| 2 conductors with same cross section, stranded, ferrules without plastic sleeve, max.   | 1.5 mm <sup>2</sup>  |
| Stripping length                                                                        | 8 mm                 |
| Internal cylindrical gage                                                               | A4                   |
| Screw thread                                                                            | M3                   |
| Tightening torque, min                                                                  | 0.6 Nm               |
| Tightening torque max                                                                   | 0.8 Nm               |

### Standards and Regulations

|                                        |     |
|----------------------------------------|-----|
| Connection in acc. with standard       | CSA |
| Flammability rating according to UL 94 | V0  |

## Feed-through terminal block - UK 5 BU - 3004090

### Classifications

#### eCl@ss

|            |          |
|------------|----------|
| eCl@ss 4.0 | 27141120 |
| eCl@ss 4.1 | 27141120 |
| eCl@ss 5.0 | 27141120 |
| eCl@ss 5.1 | 27141120 |
| eCl@ss 6.0 | 27141120 |
| eCl@ss 7.0 | 27141120 |
| eCl@ss 8.0 | 27141120 |
| eCl@ss 9.0 | 27141120 |

#### ETIM

|          |          |
|----------|----------|
| ETIM 2.0 | EC000897 |
| ETIM 3.0 | EC000897 |
| ETIM 4.0 | EC000897 |
| ETIM 5.0 | EC000897 |

#### UNSPSC

|               |          |
|---------------|----------|
| UNSPSC 6.01   | 30211811 |
| UNSPSC 7.0901 | 39121410 |
| UNSPSC 11     | 39121410 |
| UNSPSC 12.01  | 39121410 |
| UNSPSC 13.2   | 39121410 |

### Approvals

#### Approvals

---

##### Approvals

CSA / cUL Recognized / GL / DNV / RS / EAC

---

##### Ex Approvals

---

##### Approvals submitted

---

##### Approval details

## Feed-through terminal block - UK 5 BU - 3004090

### Approvals

|                                                                                       |       |
|---------------------------------------------------------------------------------------|-------|
| CSA  |       |
| mm²/AWG/kcmil                                                                         | 28-10 |
| Nominal current I <sub>N</sub>                                                        | 40 A  |
| Nominal voltage U <sub>N</sub>                                                        | 600 V |

|                                                                                                  |       |
|--------------------------------------------------------------------------------------------------|-------|
| cUL Recognized  |       |
| mm²/AWG/kcmil                                                                                    | 26-10 |
| Nominal current I <sub>N</sub>                                                                   | 30 A  |
| Nominal voltage U <sub>N</sub>                                                                   | 600 V |

|    |
|----|
| GL |
|----|

|     |
|-----|
| DNV |
|-----|

|    |
|----|
| RS |
|----|

|     |
|-----|
| EAC |
|-----|