

Fuse - FUSE 10,3X85 25A PV - 3062774

Please be informed that the data shown in this PDF Document is generated from our Online Catalog. Please find the complete data in the user's documentation. Our General Terms of Use for Downloads are valid (<http://phoenixcontact.com/download>)



Fuse, 10.3 mm x 85 mm, up to 1200 V DC, gPV characteristic

Your advantages

- ✓ 10 x 85 midjet fuses for reliable protection of PV modules and their control system
- ✓ Use in PV lines with a nominal voltage of up to 1500 V DC
- ✓ Designed in accordance with the photovoltaic standard IEC 60269-6

RoHS

Key Commercial Data

Packing unit	1 pc
Minimum order quantity	10 pc
GTIN	 4 046356 669603
GTIN	4046356669603
Weight per Piece (excluding packing)	16.000 g
Custom tariff number	85351000
Country of origin	Slovenia

Technical data

General

Color	white
Flammability rating according to UL 94	V0

Dimensions

Length	85 mm
Diameter	10.3 mm

Fuse - FUSE 10,3X85 25A PV - 3062774

Technical data

General

Fuse	Midget/10.3 x 85
Connection in acc. with standard	IEC 60269-6
Nominal current I_N	25 A
Nominal voltage U_N	1200 V DC

Standards and Regulations

Connection in acc. with standard	IEC 60269-6
Flammability rating according to UL 94	V0

Environmental Product Compliance

China RoHS	Environmentally friendly use period: unlimited = EFUP-e
	No hazardous substances above threshold values

Classifications

eCl@ss

eCl@ss 4.0	27142001
eCl@ss 4.1	27142001
eCl@ss 5.0	27142001
eCl@ss 5.1	27142000
eCl@ss 6.0	27142000
eCl@ss 7.0	27142002
eCl@ss 8.0	27142002
eCl@ss 9.0	27142002

ETIM

ETIM 3.0	EC000035
ETIM 4.0	EC002704
ETIM 5.0	EC002704
ETIM 6.0	EC002704
ETIM 7.0	EC002704

UNSPSC

UNSPSC 6.01	30211915
UNSPSC 7.0901	39121514
UNSPSC 11	39121514
UNSPSC 12.01	39121514
UNSPSC 13.2	39121627



Fuse - FUSE 10,3X85 25A PV - 3062774

Approvals

Approvals

Approvals

EAC

Ex Approvals

Approval details

EAC		RU C- DE.A*30.B.01742
-----	---	--------------------------