

Please be informed that the data shown in this PDF Document is generated from our Online Catalog. Please find the complete data in the user's documentation. Our General Terms of Use for Downloads are valid (http://phoenixcontact.com/download)



Ferrule, Sleeve length: 18 mm, Length: 28 mm, Color: red

The figure shows the version Al 1-6 RD $\,$

Product Features

- The ferrules with plastic sleeve are made from soft tin-plated electrolytic copper
- The Al 0,25.. ferrules can also be used to process 0.14 mm² conductors
- The insulation reliability of close connections is increased and the splicing of wires is prevented



Key Commercial Data

Packing unit	1 pc
Minimum order quantity	100 pc
GTIN	4 017918 094225
Weight per Piece (excluding packing)	0.662 g
Custom tariff number	85369010
Country of origin	Germany

Technical data

Dimensions

Length (b)	28 mm
Maximum stripping length	21 mm
Sleeve length	18 mm
Inner dimension of the insulating collar (d)	7.5 mm
Ferrule diameter	4.6 mm
Insulating collar thickness	0.3 mm



Technical data

Dimensions

Sleeve wall thickness	0.2 mm	
Ambient conditions		

Short-term temperature	120 °C
Max. permanent temperature	105 °C

General

Color	red
Components	free from silicone and halogen
Flammability rating according to UL 94	НВ
Material	E-CU
Coating	tin-plated (galvanic)

Standards and Regulations

Connection in acc. with standard	CSA
Flammability rating according to UL 94	НВ

Classifications

eCl@ss

eCl@ss 4.0	27060701
eCl@ss 4.1	27060701
eCl@ss 5.0	27400201
eCl@ss 5.1	27400201
eCl@ss 6.0	27400201
eCl@ss 7.0	27400201
eCI@ss 8.0	27400201

ETIM

ETIM 2.0	EC000005
ETIM 3.0	EC000005
ETIM 4.0	EC000005
ETIM 5.0	EC000005

UNSPSC

UNSPSC 6.01	30212109
UNSPSC 7.0901	27121703
UNSPSC 11	27121703
UNSPSC 12.01	27121703




Classifications

UNSPSC		
UNSPSC 13.2	27121703	
Approvals		
Approvals		
Approvals		
CSA / CSAus / EAC / EAC / cCSAus		
Ex Approvals		
Approvals submitted		
Approval details		
CSA 👀		
CSAus		
EAC		
EAC		
cCSAus		

Drawings



Dimensional drawing



Phoenix Contact 2016 © - all rights reserved http://www.phoenixcontact.com