

Shield connection clamp - SKS 20-NS35 - 3240218

Please be informed that the data shown in this PDF Document is generated from our Online Catalog. Please find the complete data in the user's documentation. Our General Terms of Use for Downloads are valid (http://phoenixcontact.com/download)



Shield connection terminal block, for applying the shield to busbars

Your advantages

- The SKS ... spring shield connection clamps are available for cable and conductor diameters of 3 to 20 mm
- According to the requirements of the directive and standards for electrical equipment in potentially explosive areas, as components, shield connections are not eligible for certification. As such, shield connection clamps can be used in the Ex area even without appropriate approval and marking.
- Three different mounting types supported: on NS 35 DIN rails, on busbars or directly on conductive mounting plates



Key Commercial Data

Packing unit	1 pc
Minimum order quantity	10 pc
GTIN	4 046356 458931
GTIN	4046356458931
Weight per Piece (excluding packing)	54.000 g
Custom tariff number	85369010
Country of origin	Germany

Technical data

General

Number of levels	1
Number of connections	1
Cable diameter	5 mm 20 mm
Color	silver



Shield connection clamp - SKS 20-NS35 - 3240218

Technical data

General

Open side panel	No		
Dimensions			
Length	53.2 mm		
Width	24.7 mm		
Height	65.3 mm		
Height NS 35/7,5	68.4 mm		
Height NS 35/15	75 9 mm		

Connection data

Connection method	Spring-cage connection		
Conductor cross section solid min.	10 mm²		
Conductor cross section solid max.	20 mm ²		
Conductor cross section flexible min.	10 mm ²		
Conductor cross section flexible max.	20 mm ²		
Conductor cross section AWG min.	8		
Conductor cross section AWG max.	4		
Screw thread	M3,5		
Tightening torque, min	1 Nm		
Tightening torque max	1.2 Nm		

Environmental Product Compliance

China RoHS	Environmentally friendly use period: unlimited = EFUP-e		
	No hazardous substances above threshold values		

Classifications

eCl@ss

eCl@ss 4.0	27141100
eCl@ss 4.1	27141100
eCl@ss 5.0	27141100
eCl@ss 5.1	27141100
eCl@ss 6.0	27141100
eCl@ss 7.0	27141150
eCl@ss 8.0	27141150
eCl@ss 9.0	27141150

ETIM

ETIM 2.0	EC000897



Shield connection clamp - SKS 20-NS35 - 3240218

Classifications

ETIM

ETIM 3.0	EC000897
ETIM 4.0	EC000001
ETIM 5.0	EC002020
ETIM 6.0	EC002020
ETIM 7.0	EC002020

UNSPSC

UNSPSC 6.01	30211811
UNSPSC 7.0901	39121410
UNSPSC 11	39121410
UNSPSC 12.01	39121410
UNSPSC 13.2	39121432

Approvals

Α	р	р	r	O'	V	а	ls

Approvals

EAC

Ex Approvals

Approval details

EAC 7500651.22.01.00246

Phoenix Contact 2019 © - all rights reserved http://www.phoenixcontact.com