

Ferrule - Al 1,5-8 BK-B 2500 - 3240666

Please be informed that the data shown in this PDF Document is generated from our Online Catalog. Please find the complete data in the user's documentation. Our General Terms of Use for Downloads are valid (<http://phoenixcontact.com/download>)



Ferrules, 1.5 mm², taped, sleeve length: 8 mm, with plastic collar, galvanically tin-plated, color: black, color range according to DIN 46228-4, CSA-certified

The figure shows the Al 1-8 RD-B 3000 version

Why buy this product

- ✓ The sleeves are supplied on large reels, each containing a quantity of up to 3000
- ✓ Ferrules in tape format for automatic processing

RoHS

Key Commercial Data

Packing unit	1 STK
Minimum order quantity	2500 STK
GTIN	 4 046356 625456
GTIN	4046356625456
Weight per Piece (excluding packing)	0.130 g
Custom tariff number	85369010
Country of origin	Germany

Technical data

Dimensions

Length (b)	14 mm
Maximum stripping length	11 mm
Sleeve length	8 mm
Inner dimension of the insulating collar (d)	3.4 mm
Ferrule diameter	1.8 mm

Ferrule - AI 1,5-8 BK-B 2500 - 3240666

Technical data

Dimensions

Insulating collar thickness	0.3 mm
Sleeve wall thickness	0.15 mm

Ambient conditions

Short-term temperature	120 °C
Max. permanent temperature	105 °C

General

Color	black
Components	free from silicone and halogen
Flammability rating according to UL 94	HB
Material	E-CU
Coating	tin-plated (galvanic)

Standards and Regulations

Connection in acc. with standard	CSA
Flammability rating according to UL 94	HB

Environmental Product Compliance

China RoHS	Environmentally friendly use period: unlimited = EFUP-e
	No hazardous substances above threshold values

Drawings

Dimensional
drawing

Approvals

Approvals

Approvals

CSA / CSAus / EAC / EAC / cCSAus

Ex Approvals

Approval details

Ferrule - AI 1,5-8 BK-B 2500 - 3240666

Approvals

CSA  <http://www.csagroup.org/services/testing-and-certification/certified-product-listing/247397>

CSAus <http://www.csagroup.org/services/testing-and-certification/certified-product-listing/247397>

EAC EAC-Zulassung

EAC 7500651.22.01.00246

cCSAus <http://www.csagroup.org/us/en/services/testing-and-certification/certified-product-listing>