

Ferrule - A 70 -40 - 3241241

Please be informed that the data shown in this PDF Document is generated from our Online Catalog. Please find the complete data in the user's documentation. Our General Terms of Use for Downloads are valid (<http://phoenixcontact.com/download>)



Ferrule, Sleeve length: 40 mm, Length: 40 mm, Color: silver

The figure shows variant A 1-6

Why buy this product

- ✓ The dimensions of the ferrules conform to DIN 46228-1
- ✓ The ferrules without plastic sleeve are made from soft tin-plated electrolytic copper

RoHS

Key Commercial Data

Packing unit	1 STK
Minimum order quantity	100 STK
GTIN	 4 046356 908146
GTIN	4046356908146
Weight per Piece (excluding packing)	5.800 g
Custom tariff number	85369010
Country of origin	Germany

Technical data

Dimensions

Length (b)	40 mm
Maximum stripping length	40 mm
Sleeve length	40 mm
Inner dimension of the insulating collar (d)	15 mm
Ferrule diameter	12.5 mm
Sleeve wall thickness	0.4 mm

Ferrule - A 70 -40 - 3241241

Technical data

Ambient conditions

Short-term temperature	120 °C
Max. permanent temperature	105 °C

General

Color	silver
Material	E-CU
Coating	tin-plated (galvanic)

Environmental Product Compliance

China RoHS	Environmentally friendly use period: unlimited = EFUP-e
	No hazardous substances above threshold values

Classifications

eCl@ss

eCl@ss 4.1	27060701
eCl@ss 5.1	27400201
eCl@ss 6.0	27400201
eCl@ss 8.0	27400201
eCl@ss 9.0	27400201

ETIM

ETIM 5.0	EC000005
ETIM 6.0	EC000005

UNSPSC

UNSPSC 13.2	27121703
-------------	----------

Accessories

Accessories

Crimping tool

Crimping pliers - CRIMPFOX-C120 - 1212318



Basic pliers, for accommodating dies for a wide range of type of contacts up to 120 mm²

Ferrule - A 70 -40 - 3241241

Accessories

Die

Replacement die - CRIMPFOX-C120 AI 70/M-DIE - 1212335



Die (upper part), for CRIMPFOX-C120, for ferrules (DIN 46228) 70 mm², trapeze crimp

Replacement die - CRIMPFOX-C120 AI 70/F-DIE - 1212338



Die (lower part), for CRIMPFOX-C120, for ferrules (DIN 46228) 70 mm², trapeze crimp
