

Thermal transfer printer - THERMOMARK ROLL X1 - 5146723

Please be informed that the data shown in this PDF Document is generated from our Online Catalog. Please find the complete data in the user's documentation. Our General Terms of Use for Downloads are valid (<http://phoenixcontact.com/download>)



Thermal transfer printer for material off the roll up to a diameter of 200 mm

Product Features

- Maintenance-free operation with proven thermal transfer printing technology
- Easy to control with the CLIP PROJECT software
- For all labels and shrink sleeves
- Easy operating concept based on user-friendly touch screen entry
- High-quality, fast labeling
- The THERMOMARK ROLL can print markers supplied in roll format for terminal, conductor, cable, and device marking applications
- USB and Ethernet connections

Key Commercial Data

Packing unit	1 pc
Custom tariff number	84433210
Country of origin	Germany

Technical data

General

Interface	10/100 Mbps Ethernet
	USB 2.0
Weight	5.00 kg

Dimensions

Length	412.00 mm
Height	245.00 mm
Width	264.00 mm

Connection data

Minimum voltage	100 V AC
Max. voltage	240 V AC

Thermal transfer printer - THERMOMARK ROLL X1 - 5146723

Technical data

Connection data

Additional text	50 Hz ... 60 Hz
-----------------	-----------------

Classifications

eCl@ss

eCl@ss 4.0	27060701
eCl@ss 4.1	27060701
eCl@ss 5.0	27400201
eCl@ss 5.1	27400201
eCl@ss 6.0	27400201
eCl@ss 7.0	27400201
eCl@ss 8.0	19140104
eCl@ss 9.0	19140104

ETIM

ETIM 3.0	EC000761
ETIM 4.0	EC001672
ETIM 5.0	EC001672

UNSPSC

UNSPSC 6.01	27121706
UNSPSC 7.0901	27121706
UNSPSC 11	27121706
UNSPSC 12.01	27121706
UNSPSC 13.2	27121706

Approvals

Approvals

Approvals

UL Listed / cUL Listed / IECCEB Scheme / EAC / CCC / cULus Listed

Ex Approvals

Approvals submitted

Thermal transfer printer - THERMOMARK ROLL X1 - 5146723

Approvals

Approval details

UL Listed 

cUL Listed 

IECEE CB Scheme 

EAC

CCC

cULus Listed 