

Control cabinet feed-through - CUC-BH-M12A1PBK-S/R4BE - 1414396

Please be informed that the data shown in this PDF Document is generated from our Online Catalog. Please find the complete data in the user's documentation. Our General Terms of Use for Downloads are valid (<http://phoenixcontact.com/download>)



Control cabinet feed-through, M12, 8-pos., A-coded on RJ45 socket, socket input 180°, IP65/67

Why buy this product

- Compact design
- 1 Gbps
- IP65/67
- UL



Key Commercial Data

Packing unit	1 STK
GTIN	 4 055626 166766

Technical data

Mechanical characteristics

Number of positions	8
Shielded	yes
Insertion/withdrawal cycles	≥ 100
Cable exit	straight
Color	black
Mounting type	Rear mounting

Ambient conditions

Ambient temperature (operation)	-25 °C ... 85 °C
---------------------------------	------------------

Material data

Flammability rating according to UL 94	V0
Housing material	PA
Contact material	Copper alloy

Electrical characteristics

Control cabinet feed-through - CUC-BH-M12A1PBK-S/R4BE - 1414396

Technical data

Electrical characteristics

Number of positions	8
Nominal voltage U_N	60 V
Nominal current I_N	0.5 A
Transmission characteristics (category)	CAT5 (IEC 11801:2002)
Rated current	1.75 A

Standards and Regulations

Flammability rating according to UL 94	V0
--	----

Classifications

eCl@ss

eCl@ss 8.0	27141134
------------	----------

ETIM

ETIM 5.0	EC001283
----------	----------

Approvals

Approvals

Approvals

EAC / UL Listed / cUL Listed / cULus Listed

Ex Approvals

Approvals submitted

Approval details

EAC

UL Listed 	
Nominal current I_N	0.5 A
Nominal voltage U_N	60 V

Control cabinet feed-through - CUC-BH-M12A1PBK-S/R4BE - 1414396

Approvals

cUL Listed 	
Nominal current I _N	0.5 A
Nominal voltage U _N	60 V


cULus Listed 	
--	--

Drawings

Exposition
drawing


Exploited
drawing

Dimensional drawing



Panel cutout

Dimensional drawing



Panel cutout

Phoenix Contact 2016 © - all rights reserved
<http://www.phoenixcontact.com>

PHOENIX CONTACT GmbH & Co. KG
Flachsmarktstr. 8
32825 Blomberg
Germany
Tel. +49 5235 300
Fax +49 5235 3 41200
<http://www.phoenixcontact.com>