

Fiber optic coupling - FL SM PATCH COUPLER LC-LC - 2700313

Please be informed that the data shown in this PDF Document is generated from our Online Catalog. Please find the complete data in the user's documentation. Our General Terms of Use for Downloads are valid (<http://phoenixcontact.com/download>)



Coupling, LC/LC, can be used for single mode glass fibers

Key Commercial Data

Packing unit	1 STK
GTIN	 4 046356 543019

Technical data

Mechanical characteristics

Number of positions	2
Number of slots	1
Connection profile	LC-Duplex
Fiber type	Single-mode fiberglass
Fiber	9/125 µm
Number of fibers	2
Insertion/withdrawal cycles	≥ 500
Connection method	Coupling

Ambient conditions

Ambient temperature (operation)	-25 °C ... 70 °C
---------------------------------	------------------

Material data

Flammability rating according to UL 94	V0
Housing material	PBT
Ferrule material	Zirconia ceramics
Ferrule holder color	white

Standards and Regulations

Flammability rating according to UL 94	V0
--	----

Fiber optic coupling - FL SM PATCH COUPLER LC-LC - 2700313

Classifications

eCl@ss

eCl@ss 4.0	27250315
eCl@ss 4.1	27250315
eCl@ss 5.0	27249290
eCl@ss 5.1	27249290
eCl@ss 6.0	27249290
eCl@ss 7.0	27249290
eCl@ss 8.0	19170116

ETIM

ETIM 3.0	EC000313
ETIM 4.0	EC002584
ETIM 5.0	EC000752

UNSPSC

UNSPSC 6.01	43172015
UNSPSC 7.0901	43201404
UNSPSC 11	39121311
UNSPSC 12.01	39121311
UNSPSC 13.2	39121311

Phoenix Contact 2016 © - all rights reserved
<http://www.phoenixcontact.com>

PHOENIX CONTACT GmbH & Co. KG
Flachsmarktstr. 8
32825 Blomberg
Germany
Tel. +49 5235 300
Fax +49 5235 3 41200
<http://www.phoenixcontact.com>