

Shield connection terminal block - SKS 14-NS35 - 3240217

Please be informed that the data shown in this PDF Document is generated from our Online Catalog. Please find the complete data in the user's documentation. Our General Terms of Use for Downloads are valid (<http://phoenixcontact.com/download>)



Shield connection terminal block, for applying the shield to busbars

Why buy this product

- The SKS ... spring shield connection clamps are available for cable and conductor diameters of 3 to 20 mm
- According to the requirements of the directive and standards for electrical equipment in potentially explosive areas, as components, shield connections are not able to gain certification. As such, shield connection clamps of type SKS can be used in the Ex area even without appropriate approval and identification.
- Three different mounting types supported: on NS 35 DIN rails, on busbars or directly on conductive mounting plates
- The SKS ... spring shield connection clamps are available for cable and conductor diameters of 3 to 20 mm

Key Commercial Data

Packing unit	10 STK
GTIN	 4 046356 458900

Technical data

General

Number of levels	1
Number of connections	1
Cable diameter	3 mm ... 14 mm
Color	silver

Dimensions

Length	53.2 mm
Width	19 mm
Height	56.80 mm
Height NS 35/7,5	60 mm

Connection data

Conductor cross section solid min.	4 mm ²
Conductor cross section solid max.	13.5 mm ²
Conductor cross section flexible min.	4 mm ²
Conductor cross section flexible max.	13.5 mm ²
Conductor cross section AWG min.	10

Shield connection terminal block - SKS 14-NS35 - 3240217

Technical data

Connection data

Conductor cross section AWG max.	6
Connection method	Spring-cage

Classifications

eCl@ss

eCl@ss 4.0	27141131
eCl@ss 4.1	27141131
eCl@ss 5.0	27141131
eCl@ss 5.1	27141131
eCl@ss 6.0	27141150
eCl@ss 7.0	27141150
eCl@ss 8.0	27141150

ETIM

ETIM 2.0	EC000897
ETIM 3.0	EC000897
ETIM 4.0	EC000001
ETIM 5.0	EC002020

UNSPSC

UNSPSC 6.01	30211811
UNSPSC 7.0901	39121410
UNSPSC 11	39121410
UNSPSC 12.01	39121410
UNSPSC 13.2	39121410

Approvals

Approvals

Approvals

EAC

Ex Approvals

Approvals submitted

Approval details

Shield connection terminal block - SKS 14-NS35 - 3240217

Approvals

EAC

Phoenix Contact 2016 © - all rights reserved
<http://www.phoenixcontact.com>

PHOENIX CONTACT GmbH & Co. KG
Flachsmarktstr. 8
32825 Blomberg
Germany
Tel. +49 5235 300
Fax +49 5235 3 41200
<http://www.phoenixcontact.com>