

# Shield connection terminal block - SKS 20-NS35 - 3240218

Please be informed that the data shown in this PDF Document is generated from our Online Catalog. Please find the complete data in the user's documentation. Our General Terms of Use for Downloads are valid (http://phoenixcontact.com/download)



Shield connection terminal block, for applying the shield to busbars

#### Why buy this product

- The SKS ... spring shield connection clamps are available for cable and conductor diameters of 3 to 20 mm
- According to the requirements of the directive and standards for electrical equipment in potentially explosive areas, as components, shield connections are not able to gain certification. As such, shield connection clamps of type SKS can be used in the Ex area even without appropriate approval and identification.
- The SKS ... spring shield connection clamps are available for cable and conductor diameters of 3 to 20 mm
- Three different mounting types supported: on NS 35 DIN rails, on busbars or directly on conductive mounting plates

## **Key Commercial Data**

Packing unit	10 STK
GTIN	4 046356 458931

## Technical data

#### General

Number of levels	1
Number of connections	1
Cable diameter	5 mm 20 mm
Color	silver

#### **Dimensions**

Length	53.2 mm
Width	24.7 mm
Height	65.30 mm
Height NS 35/7,5	68.4 mm

#### Connection data

Conductor cross section solid min.	10 mm²
Conductor cross section solid max.	20 mm <sup>2</sup>
Conductor cross section flexible min.	10 mm <sup>2</sup>
Conductor cross section flexible max.	20 mm <sup>2</sup>
Conductor cross section AWG min.	8



# Shield connection terminal block - SKS 20-NS35 - 3240218

# Technical data

## Connection data

Conductor cross section AWG max.	4
Screw thread	M3,5
Tightening torque, min	1 Nm
Tightening torque max	1.2 Nm
Connection method	Spring-cage

# Classifications

# eCl@ss

eCl@ss 4.0	27141131
eCl@ss 4.1	27141131
eCl@ss 5.0	27141131
echass 3.0	27 14 1131
eCl@ss 5.1	27141131
eci@ss 5.1	2/ 141131
eCl@ss 6.0	27141150
eoi@ss 0.0	27 141 130
eCl@ss 7.0	27141150
EOI(@33 1.0	27 141 150
eCl@ss 8.0	27141150
eciwss 6.0	27141130

### **ETIM**

ETIM 2.0	EC000897
ETIM 3.0	EC000897
ETIM 4.0	EC000001
ETIM 5.0	EC002020

## **UNSPSC**

UNSPSC 6.01	30211811
UNSPSC 7.0901	39121410
UNSPSC 11	39121410
UNSPSC 12.01	39121410
UNSPSC 13.2	39121410

# **Approvals**

### Approvals

Approvals

EAC

Ex Approvals



# Shield connection terminal block - SKS 20-NS35 - 3240218

# Approvals

Approvals submitted

Approval details

EAC

Phoenix Contact 2016 © - all rights reserved http://www.phoenixcontact.com

PHOENIX CONTACT GmbH & Co. KG Flachsmarktstr. 8 32825 Blomberg Germany

Tel. +49 5235 300 Fax +49 5235 3 41200

http://www.phoenixcontact.com