

Power supply unit - FB-PS-MB-Y/EX - 2316148

Please be informed that the data shown in this PDF Document is generated from our Online Catalog. Please find the complete data in the user's documentation. Our General Terms of Use for Downloads are valid
(<http://phoenixcontact.com/download>)

Four-channel redundant fieldbus power supply base. Host connections are for two Yokogawa AKB336 20-pin cables.



Product Description

Yokogawa four-channel, redundant fieldbus power supply base with host connectors for two AKB336 Yokogawa 20-pin cables.

Why buy this product

- ☒ Redundancy
- ☒ Built-in relay diagnostics



Key Commercial Data

Packing unit	1 STK
GTIN	 4 055626 128368
GTIN	4055626128368
Weight per Piece (excluding packing)	1.000 g
Custom tariff number	85366990
Country of origin	United States

Technical data

Note

Utilization restriction	EMC: class A product, see manufacturer's declaration in the download area
-------------------------	---

Dimensions

Width	180 mm
-------	--------

Power supply unit - FB-PS-MB-Y/EX - 2316148

Technical data

Dimensions

Height	77 mm
Depth	180 mm

Ambient conditions

Ambient temperature (operation)	-40 °C ... 70 °C
Ambient temperature (storage/transport)	-40 °C ... 85 °C
Permissible humidity (operation)	95 % (non-condensing)
Degree of protection	IP20

General

Standards/regulations	NE21
	EN 61326
Net weight	222.222 g
Conformance	CE-compliant
Fieldbus Foundation	FF-831

Power supply

Conductor cross section flexible max.	2.50 mm²
Conductor cross section flexible min.	0.20 mm²
Conductor cross section solid max.	2.50 mm²
Conductor cross section solid min.	0.20 mm²
Conductor cross section AWG max.	12
Conductor cross section AWG min.	30

Serial interface

Interface 1	Yokogawa DCS cabling system
Interface	Host system
Number of connections	2
Connection method	AKB336 cable
Torque	0.4 Nm ... 0.5 Nm (AKB336 cable)
Inductance Li	17.8 mH (trunk and host)
Max. output voltage U _o	30 V DC (trunk and host)

Digital outputs

Output name	Alarm
-------------	-------

Standards and Regulations

Type of test	Corrosive resistance in acc. to ANSI-ISA 71.04-1985 - Severity level G3
Standards/regulations	NE21
	EN 61326
Conformance	CE-compliant

Power supply unit - FB-PS-MB-Y/EX - 2316148

Technical data

Standards and Regulations

Fieldbus Foundation	FF-831
ATEX	Sira 11ATEX4216X; II 3 G Ex nA nC IIC T4 Gc
IECEX	IECEX SIR 11.0097X; Ex nA nC IIC T4 Gc
CSA, USA/Canada	Class I, Div. 2, Groups A, B, C, D; Ex nA nC IIC T4 Class I, Zone 2, AEx nA nC IIC T4

Environmental Product Compliance

REACH SVHC	Lead 7439-92-1
China RoHS	Environmentally Friendly Use Period = 50
	For details about hazardous substances go to tab "Downloads", Category "Manufacturer's declaration"

Classifications

eCl@ss

eCl@ss 7.0	27242611
eCl@ss 8.0	27242611
eCl@ss 9.0	27242692

ETIM

ETIM 4.0	EC002583
ETIM 5.0	EC001598
ETIM 6.0	EC002583