



Extract from the online
catalog

MKKDS 1,5/ 2-5,08 BK

Order No.: 1877478

<http://eshop.phoenixcontact.de/phoenix/treeViewClick.do?UID=1877478>

Printed circuit terminal block, nominal current: 17.5 A, rated voltage: 250 V, pitch: 5.08 mm, no. of positions: 2, mounting: Soldering, type of connection: Screw connection, connection direction from the conductor to the PCB: 0°

Commercial data

EAN	4017918234812
Note	Made-to-order
sales group	E020
Pack	50 pcs.
Customs tariff	85369010
Weight/Piece	0.00707 KG

Product notes

WEEE/RoHS-compliant since:
01/01/2003



<http://www.download.phoenixcontact.com>
Please note that the data given here has been taken from the online catalog. For comprehensive information and data, please refer to the user documentation. The General Terms and Conditions of Use apply to Internet downloads.

Certificates / Approvals



Certification

CCA, CSA, CUL, GOST, SEV, UL

CSA

Nominal voltage U_N	300 V
Nominal current I_N	10 A
AWG/kcmil	28-14

MKKDS 1,5/ 2-5,08 BK Order No.: 1877478

<http://eshop.phoenixcontact.de/phoenix/treeViewClick.do?UID=1877478>

CUL

Nominal voltage U_N	300 V
Nominal current I_N	10 A
AWG/kcmil	30-14

UL

Nominal voltage U_N	300 V
Nominal current I_N	10 A
AWG/kcmil	30-14

onlinecomponents.com

MKKDS 1,5/ 2-5,08 BK Order No.: 1877478
<http://eshop.phoenixcontact.de/phoenix/treeViewClick.do?UID=1877478>

Address

PHOENIX CONTACT Deutschland GmbH
Flachsmarktstr. 8
32825 Blomberg, Germany
Phone +49 5235 3 12000
Fax +49 5235 3 41200
<http://www.phoenixcontact.de>



© 2010 Phoenix Contact
Technical modifications reserved;

onlinecomponents.com