



Extract from the online
catalog

FL IF 2FX ST-D

Order No.: 2884033



<http://eshop.phoenixcontact.de/phoenix/treeViewClick.do?UID=2884033>

Interface module

Ethernet

Commercial data

EAN	4046356049498
Pack	1 pcs.
Customs tariff	85176200
Weight/Piece	0.0998 KG
Catalog page information	Page 189 (AX-2009)

Product notes

WEEE/RoHS-compliant since:
11/27/2007



<http://www.download.phoenixcontact.com>
Please note that the data given here has been taken from the online catalog. For comprehensive information and data, please refer to the user documentation. The General Terms and Conditions of Use apply to Internet downloads.

Technical data

Interfaces

Interface	Ethernet: 100Base-FX in acc. with IEEE 802.3
Transmission speed	100 MBit/s
Transmission length	10000 m (maximum (depends on the fiber used))
Interface	Ethernet: 100Base-FX in acc. with IEEE 802.3
No. of ports	2

FL IF 2FX ST-D Order No.: 2884033
http://eshop.phoenixcontact.de/phoenix/treeViewClick.do?UID=2884033

Type of connection	ST BFOC
Transmission speed	100 MBit/s
Transmission length	10000 m (glass fiber with F-G 62.5/125 0.7 dB/km F1000)
	6400 m (glass fiber with F-G 50/125 0.7 dB/km F1200)
	3000 m (glass fiber with F-G 62.5/125 2.6 dB/km F600)
	2800 m (glass fiber with F-G 50/125 1.6 dB/km F800)

Function

Basic functionality	Media module for modular managed switch
---------------------	---

Supply voltage

Supply voltage	(via head station)
Typical current consumption	200 mA

General data

Weight	80 g
Width	31 mm
Height	83 mm
Depth	72.5 mm
Degree of protection	IP20
Ambient temperature (operation)	0 °C ... 55 °C (non-condensing)
Ambient temperature (storage/transport)	-20 °C ... 70 °C
Permissible humidity (operation)	10 % ... 95 % (non-condensing)
Housing material	PA
Electromagnetic compatibility	Conformance with EMC directive 89/336/EEC
Emitted interference	EN 61000-6-3/-4
Immunity to interference	EN 61000-6-2:2005

Conformity with EMC directives

Developed in acc. with standard	IEC 61000-6.2
Test standard	IEC 61000-4-2 (ESD)
Test result	Criterion B
Test standard	IEC 61000-4-3 (immunity to radiated interference)
Test result	Criterion A
Test standard	IEC 61000-4-4 (burst)
Test result	Criterion A
Test standard	IEC 61000-4-5 (surge)

FL IF 2FX ST-D Order No.: 2884033
http://eshop.phoenixcontact.de/phoenix/treeViewClick.do?UID=2884033

Test result	Criterion A
Test standard	IEC 61000-4-6 (immunity to conducted interference)
Test result	Criterion A
Test standard	IEC 61000-4-8 (immunity to magnetic fields)
Test result	Criterion A
Test standard	EN 55022 (emitted interference)
Test result	Criterion A

Certificates / Approvals



Certification

CUL, UL

FL IF 2FX ST-D Order No.: 2884033
<http://eshop.phoenixcontact.de/phoenix/treeViewClick.do?UID=2884033>

Address

PHOENIX CONTACT GmbH & Co. KG
Flachsmarktstr. 8
32825 Blomberg, Germany
Phone +49 5235 3 00
Fax +49 5235 3 41200
<http://www.phoenixcontact.de>



© 2009 Phoenix Contact
Technical modifications reserved;

onlinecomponents.com