



Extract from the online
catalog

UM 25-D25SUB/B/FRONT/Q

Order No.: 2959609

The illustration shows the version UM 25-D 9SUB/B/FRONT/Q



<http://eshop.phoenixcontact.de/phoenix/treeViewClick.do?UID=2959609>

VARIOFACE SLIM LINE, with screw connection and D-subminiature socket strip, for assembly at a right angle on NS 35/7.5, 25 positions

Commercial data

EAN	4017918086251
Pack	1 pcs.
Customs tariff	85369010
Weight/Piece	0.2131 KG
Catalog page information	Page 287 (IF-2009)

<http://www.download.phoenixcontact.com>
Please note that the data given here has been taken from the online catalog. For comprehensive information and data, please refer to the user documentation. The General Terms and Conditions of Use apply to Internet downloads.

Technical data

General data

Nominal voltage U_N	125 V AC/DC
Max. current carrying capacity per branch	1 A (data valid for 100% coincidence factor)
Number of positions	25
Width	25 mm
Height	45 mm
Depth	217 mm
Ambient temperature (operation)	-10 °C ... 50 °C
Ambient temperature (storage/transport)	-10 °C ... 70 °C
Test voltage	800 V (50 Hz, 1 min)
Mounting position	Any

UM 25-D25SUB/B/FRONT/Q Order No.: 2959609
http://eshop.phoenixcontact.de/phoenix/treeViewClick.do?UID=2959609

Standards/regulations	IEC 60664
	IEC 60664 A
	DIN VDE 0110
	DIN VDE 0160 (in parts)
Pollution degree	2
Surge voltage category	II

Connection data

Connection 1	PCB connection
Connection in acc. with standard	IEC / EN
Type of connection	Screw connection
Conductor cross section solid min.	0.2 mm ²
Conductor cross section solid max.	4 mm ²
Conductor cross section stranded min.	0.2 mm ²
Conductor cross section stranded max.	2.5 mm ²
Conductor cross section AWG/kcmil min.	24
Conductor cross section AWG/kcmil max	12
Stripping length	8 mm
Screw thread	M3
Connection 2	D-SUB connection
Type of connection	Pluggable

Certificates / Approvals




Certification

GOST

UM 25-D25SUB/B/FRONT/Q Order No.: 2959609
<http://eshop.phoenixcontact.de/phoenix/treeViewClick.do?UID=2959609>

Drawings

Circuit diagram



UM 25-D25SUB/B/FRONT/Q Order No.: 2959609
<http://eshop.phoenixcontact.de/phoenix/treeViewClick.do?UID=2959609>

Address

PHOENIX CONTACT GmbH & Co. KG
Flachsmarktstr. 8
32825 Blomberg, Germany
Phone +49 5235 3 00
Fax +49 5235 3 41200
<http://www.phoenixcontact.de>



© 2009 Phoenix Contact
Technical modifications reserved;

onlinecomponents.com