

			PWOUT FIBER	)	F612D3-NM6	+			[6 meters]	[1444.8g/10 pcs.] 5.24 lb/10 pcs. [2383.2/10 pcs.] 8.00 lb/10 pcs. [3634.4/10 pcs.]	SC CERAMI	
	12-FIBER OPANICE JACKETED DISER DATED											
	12-FIBER ORANGE JACKETED RISER RATED BUFFERED MULTIMODE FIBER OPTIC DISTRIBUTION CABLE											
H	NOTES:  1. SEE CURRENT CATALOG FOR PACKAGE QUANTITY.  2. 12 FIBER BUFFERED MULTIMODE 62.5/125UM GLASS OPTICAL FIBER DISTRIBUTION CABLE, RISER RATED  3. TERMINATED WITH SC CONNECTORS.  4. ASSEMBLED WITH TEMPERATURE CURED EPOXY.  5. JACKET COLOR IS ORANGE.										25UM GLASS RISER RATED.	
				27.0" <sup>+0</sup> -1.5 [685.8 <sup>+0</sup> -38]		6. <sup>-</sup>	THE I IS .: DUST	MAXII 35dB CAP	S (NOT SHOW	ON LOSS PER CONI N) INSTALLED ON RACKETS ARE METI	ALL CONNECTO	RS.
٥	٥٥٥	ŮŮ	٥٥						CAD FILENMEZAYERS	M00997BM_D0		
					MBLY SHIPPED WITH PS(NOT SHOWN)				PRETERMINATED 12 STRAND MULTIMODE FIBER OPTIC PIGTAIL (F612D3 SERIES) CUSTOMER DRAWING			
									UNLESS OTHERW DIMENSIONAL TO (.X) ± .06[1]	ISE SPECIFIED, OLERANCES ARE: .5] (.XXX) ±	UNLESS OTHERWISE SPECIFIED, ALL DIMENSIONS ARE GIVEN	
						ı			(.XX) ±	ANGLES ±	IN INCHES, THIRD MILE PROJEC	CT ICOL.
R	11-27-00			RELEASED FOR PRODUCTION	00997-17				EFK MAT'	AS NOTED	SCALE NONE	DNS