+

THIS COPY IS PROVIDED ON A RESTRICTED BASIS AND IS NOT TO BE USED IN ANY WAY DETRIMENTAL TO THE INTERESTS OF PANDUIT CORP. PRINTED -PRINTED NOTES: CABLE CABLE 1. SEE SHEET 2 FOR PRODUCT DESCRIPTIONS AND TECHNICAL SPECIFICATIONS. 2. SEE CURRENT CATALOG FOR PATCH CORD LENGTHS AND PACKAGE QUANTITY. 3. FOR LENGTHS OTHER THAN THOSE LISTED IN CATALOG, CONTACT YOUR PANDUIT SALES PERSON. 4. TESTED TO EIA/TIA 568-B.3. 5. PATCH CORD ROUTING CONFIGURATION A TO B. 6. ALL MATERIALS AND COMPONENTS USED MEET THE MATERIAL RESTRICTIONS OF ROHS, (EUROPEAN DIRECTIVE 2002/95/EC ON THE RESTRICTION OF HAZARDOUS SUBSTANCES) AS PROPOSED BY THE ROHS TECHNICAL ADAPTATION COMMITTEE. DUPLEX OPTI-PLUG KEYED SC DUPLEXING ** W ** "X" "Y" "フ" CLIP "A" & "B" DESIGNATION ON TOP OF BOOT FRONT VIEWS SHOWING KEY CONFIGURATION - SCALE: 2:1 DUPLEX FIBER OPTIC PATCH CORD OPT I - PLUG SC CONNECTORS OPTI-PLUG KEYED TO SC CONNECTOR CONFIGURATION CUSTOMER DRAWING CORP. TINLEY PARK, ILL 60477 DRAWING FILENAME ALL DIMENSIONS ARE GIVEN IN INCHES, UNLESS OTHERWISE SPECIFIED. M02779BP_DC_00A.prt DIMENSIONAL TOLERANCES ARE: SCALE (.X) (.XXX) NONE THIRD ANGLE (.XX) **ANGLES** PART NO. DRAWN BY REVIEW DRAWING NUMBERS SEE TABLE, SHT. 2 DRAWING NO. SIZE MC 06-06-07 RELEASED TO PRODUCTION 02779-21 AS NOTED 05-14-07 02779-21 CHK 'D

SUP

CUST

ECN - R

ОТН

(SHT. 1 of 2)

.

REV

DATE

BY CHK

DESCRIPTION

Η_

06-06-07 MC

BY CHK

DATE

RELEASED TO PRODUCTION

DESCRIPTION

4

THIS COPY IS PROVIDED ON A RESTRICTED BASIS AND IS NOT TO BE USED IN ANY WAY DETRIMENTAL TO THE INTERESTS OF PANDUIT CORP.

			75 NOT 10								
		DUPLEX	ST TO SC	FIBER	OPTIC PA	ATCH CORD					
PANDUIT PART NO.	CABLE				OPTI-PLUG KEYED			SC CONNECTOR			
	RATING	FIBER TYPE	COUNT	COLOR	MAX. IL	_ MIN. RL	COLOR	MAX. IL	MIN. RL	COLOR	
FXD6PW-3M*Y	RISER (OFNR)	10 GbE 50/125um OM3	DUPLEX 3.0mm ZIPCORD	AQUA	0.30dB	26dB	BLACK	0.30dB	26dB	ELECTRIC I VORY	
F5D6PW-3M*Y		50/125um OM2		ORANGE	0.30dB	20dB	BLACK	0.30dB	20dB	ELECTRIC I VORY	
F6D6PW-3M*Y		62.5/125um OMI		ORANGE	0.30dB	20dB	BLACK	0.30dB	20dB	ELECTRIC IVORY	
FXD6PX-3M*Y "X"	RISER (OFNR)	10 GbE 50/125um OM3	DUPLEX 3.0mm ZIPCORD	AQUA	0.30dB	26dB	RED	0.30dB	26dB	ELECTRIC IVORY	
F5D6PX-3M*Y "X"		50/125um OM2		ORANGE	0.30dB	20dB	RED	0.30dB	20dB	ELECTRIC IVORY	
F6D6PX-3M*Y "X"		62.5/125um OMI		ORANGE	0.30dB	20dB	RED	0.30dB	20dB	ELECTRIC IVORY	
FXD6PY-3M*Y	RISER (OFNR)	10 GbE 50/125um OM3	DUPLEX 3.0mm ZIPCORD	AQUA	0.30dB	26dB	ORANGE	0.30dB	26dB	ELECTRIC IVORY	
F5D6PY-3M*Y		50/125um OM2		ORANGE	0.30dB	20dB	ORANGE	0.30dB	20dB	ELECTRIC IVORY	
F6D6PY-3M*Y		62.5/125um OMI		ORANGE	0.30dB	20dB	ORANGE	0.30dB	20dB	ELECTRIC IVORY	
FXD6PZ-3M*Y	RISER (OFNR)	10 GbE 50/125um OM3	DUPLEX 3.0mm ZIPCORD	AQUA	0.30dB	26dB	YELLOW	0.30dB	26dB	ELECTRIC I VORY	
F5D6PZ-3M*Y "Z"		50/125um OM2		ORANGE	0.30dB	20dB	YELLOW	0.30dB	20dB	ELECTRIC IVORY	
F6D6PZ-3M*Y "Z"		62.5/125um OMI		ORANGE	0.30dB	20dB	YELLOW	0.30dB	20dB	ELECTRIC IVORY	
* - DENOTES PATCH CORD LENGTH, WHERE M = METERS AND F = FEET											
						DUPLEX FIBER OPTIC PATCH CORD OPTI-PLUG KEYED TO SC CONNECTOR CONFIGURATION CUSTOMER DRAWING					
							TINLEY PARK, ILL 60477				
						x	ALL DIMENSIONS ARE GIVEN IN INCHES UNLESS OTHERWISE SPECIFIED. DIMENSIONAL TOLERANCES ARE: [.XXXX1:.010 0.3] DRAWING FILENAME MO2779BP_DC_00A.pr				
					DF	PROJECTION 1.X	REVIEW DRAWING NUMBERS REVIEW DRAWING NUMBERS PART NO. SEE TABLE				

CUST SUP

02779-21

ECN - R

05 - 14 - 07

DRAWING NO.

02779-21

(SHT. 2 of 2)

AS NOTED

SIZE