


NOTES:

1. MADE FROM HIGH COPPER CONTENT ALLOY. FURNISHED WITH FULL THREADED SILICON BOLT, NUTS, AND LOCKWASHERS.
2. THESE CONNECTORS ARE UL LISTED FOR GROUNDING AND BONDING, AND DIRECT BURIAL APPLICATIONS.
3. PACKAGE QTY: -Q = 25
-X = 10

PANDUIT PART NUMBER	CONDUCTOR RANGE	DIMENSIONS							BOLT DIA.
		A		B		C			
		IN	MM	IN	MM	IN	MM		
GMS-1-X	8 SOL. - 4 STR.	1.25	32	1.00	25	1.63	41	0.38	
GMS-2-Q	4 SOL. - 2/0 STR	1.63	41	1.13	28	1.75	44	0.38	
GMS-3-Q	2/0 STR. - 250 kcmil	2.13	54	1.50	38	2.00	51	0.50	

04	12/08	JHNU	JHNU	REVISED PART NUMBERS: GMS1-X,GMS2-Q, & GMS3-Q WERE GM-1-X, GM2-Q, & GM3-Q		
03	10/08	JHNU	JHNU	REVISED UL LISTING CONVERTED DWG. TO SOLIDWORKS		
02	11/02	CJW		ADDED GMS-1-X & ADDED X=10 TO NOTE #3 CHANGED MCM TO KCMIL		
01	1/01	EJS	WJB	ADDED PACKAGE CODE TO PART NUMBER, ADDED NOTE 3, REVISED UL LISTING, FILE SPEC WAS N41170CA_PCD_00		
00	10/95	ED	WJB	DWG. RELEASED	03703	
REV	DATE	BY	CHK	DESCRIPTION	ECN	SCALE
						N/A
						DRAWING NO / CAD FILE
						C41170_04

PANDUIT CORP. TINLEY PARK, ILLINOIS

BRONZE GROUND CLAMP CONNECTOR, GMS SERIES
CUSTOMER DRAWING