


|                                                      |                                                                                                                                                            |
|------------------------------------------------------|------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Material                                             | High Conductivity<br>Seamless Copper Tube                                                                                                                  |
| Plating                                              | Electro-Tin                                                                                                                                                |
| Wire Size & Type                                     | Stranded Copper Flex Cable;<br>4/0 AWG (550/24) Diesel<br>Locomotive, 4/0 AWG FLEX K,M<br>Class K & Class M                                                |
| Wire Strip Length                                    | 1-7/16 in.                                                                                                                                                 |
| Stud Size                                            | 5/16 in.                                                                                                                                                   |
| UL Listed Wire<br>Connector                          | Yes, for applications up to 35kv.<br>Consult cable manufacturer for<br>voltage stress relief instructions<br>with applications greater than<br>2000 volts. |
| UL Temperature<br>Rating                             | 90° C                                                                                                                                                      |
| C.S.A Certified<br>Wire Connector                    | Yes                                                                                                                                                        |
| Panduit Color Code<br>on Barrel                      | YELLOW                                                                                                                                                     |
| Panduit Die Index No.<br>on Barrel                   | P62                                                                                                                                                        |
| Alternate Industry<br>Die Index No. ( )<br>on Barrel | (16)                                                                                                                                                       |



|     |      |     |     |             |       |                                                                                                                                  |                                          |
|-----|------|-----|-----|-------------|-------|----------------------------------------------------------------------------------------------------------------------------------|------------------------------------------|
|     |      |     |     |             |       |  <b>PANDUIT CORP. TINLEY PARK, ILLINOIS</b> |                                          |
|     |      |     |     |             |       | LCAF4/0-56-X<br>Copper Lug - One-Hole, Flared Barrel                                                                             |                                          |
| 00  | 9/02 | SAB | DRL | RELEASED    | 10321 |                                                                                                                                  |                                          |
| REV | DATE | BY  | CHK | DESCRIPTION | ECN   | SCALE<br>N/A                                                                                                                     | DRAWING NO / CAD FILE<br>LCAF4_0-56-CUST |