

Search Results

Your search criteria matched only one product, shown below

ABDCM30-A-E



- Unique mount design transfers the dynamic load of the bundle away from the edge of the mount, preventing the mount from peeling off of the panel surface
- Ball-and-socket tether retains position of bundle relative to hinge while opening and closing panel door(s), eliminating the risk for potential shocks and shorts that could damage internal components
- Universal slot design permits use of any cable tie with a 50 lb. minimum loop tensile strength, providing design flexibility

Part Number	ABDCM30A-E
RoHS Compliancy Status	Compliant
Part Description	Dynamic Cable Manager for Panel Strain Relief
Product Type	Cable Tie Mounts- Adhesive Backed
Material	Nylon 6.6
Color	White
Height (In.)	0.66
Height (mm)	16.8
Length (In.)	1.12
Length (mm)	28.4
Width (In.)	1.12
Width (mm)	28.4
Environment	Indoor
Flammability Rating	V-2
Mounting Method	Rubber Adhesive Tape
Overall Size W x H (In.)	1.98" x .66"
Overall Size W x H (mm)	50.3mm x 16.8mm
Pricing Description	Dynamic Cable Manager, 1.12" x 1.12" (28.4mm x 28.4mm), Nylon 6.6, White, 20/pkg
Temperature Range	-40°F– 120°F (-40°C– 49°C)
Type	Cable Tie Mounts- Adhesive Backed
Used With Cable Ties	M, I, S
Min. Order UOM	PC
Min. Order Qty.	20
BOM Qty. (# of Pkgs.)	0
Add to Favorite Product List	e

Please [register](#) to utilize the 'Bill of Materials', 'Submit Quotes' and 'Favorite Product List' features.