



Search Results

Evaluate

- Advertisements
- PDF-Energy Effic ..
- Brochures
- PDF-Energy Effic ..
- FAQ's

Design a Solution

- Catalog Cut Sheet
- PDF-CN3847018NU
- Part Drawings
- DXF-NET-ACCESS C ..
- DWG-NET-ACCESS C ..
- PDF-NET-ACCESS C ..
- Specification Sheets
- PDF-Thermal Inle ..
- PDF-CabRunner Ov ..
- PDF-Thermal Inle ..
- PDF-Net-Access E ..
- PDF-Net-Access V ..
- PDF-Net-Access E ..
- PDF-Thermal Inle ..

How to Buy

- Bill of Material
- Favorite Products List
- Locate Distributor

Install & Maintain

- Installation Instructions
- PDF-Net-Access V ..

Home > Product On-Line Catalog > Search Results >

Current refinements (click to remove) [Search Tips](#)

Text Search: 'CVED32VES'

Your search criteria matched only one product, shown below

CVED32VES



- Support 30+ KW heat loads
- Passive duct solutions do not require additional energy consumption
- Designed using CFD (Computational Fluid Dynamics) validating thermal performance
- Directly vents hot air exhaust to data center air return plenum
- Foam seal minimizes leakage against air return plenum interface
- Black powder coat finish

▪ Part Number	CVED32VES
▪ RoHS Compliancy Status	Compliant
▪ Part Description	Variable short duct extension is infinitely adjustable between 20.0" (508mm) to 36.0" (914mm).
▪ Color	Black
▪ Pricing Description	Net-Access Variable duct extension will infinitely adjust from 20.0" to 34.0"
▪ Min. Order UOM	PC
▪ Min. Order Qty.	1
▪ BOM Qty. (# of Pkgs.)	0
▪ Add to Favorite Product List	☐

Please [register](#) to utilize the 'Bill of Materials', 'Submit Quotes' and 'Favorite Product List' features.