Search Results

Evaluate
- FAQ's
- Line Cards
- PDF-Cable Access ..

Design a Solution
- Catalog Cut Sheet
- PDF-BR-.50 Produ
- PDF-BR-.50 Produ
- Part Drawings
- PDF-Bridle Ring..
- Specification Sheets
- PDF-Cable Access ..

How to Buy
- Bill of Material
- Favorite Products List
- Locate Distributor

Current refinements (click ☒ to remove) Search Tips

☒ **Text Search: 'BR-1.25-1/4-20'**

Your search criteria matched only one product, shown below

BR-1.25-1/4-20

- Multiple diameters, thread sizes, and configurations
- Threaded and non -threaded sizes are compatible with spring steel clip (BR -MPCL) clamp providing a solid securing point for the bridle ring
- Other unique labor saving assemblies differentiate from competition – including pre - assemblies with powder actuated fasteners, toggle wings, and clearance holes for user supplied fasteners

Part Number	BR-1.25-1/4-20
RoHS Compliancy Status	RoHS directive is not applicable
Part Description	Bridle ring, 1.25" dia., 1/4– 20 threaded.
Material	Low carbon steel with bright zinc electroplate
Max. Bundle Capacity (In.)	1.25
Max. Bundle Capacity (mm)	32
Overall Height (In.)	3.0
Overall Height (mm)	77
Pricing Description	Bridle Ring, 1.25" Dia., 1/4- 20 Threaded
Ring Size	1 1/4"
Thread size	1/4"– 20 threaded
Min. Order UOM	PC
Min. Order Qty.	100
BOM Qty. (# of Pkgs.)	0
Add to Favorite Product List	e

Please register to utilize the 'Bill of Materials', 'Submit Quotes' and 'Favorite Product List' features.

Copyright © 1995-2011, PANDUIT CORP. All rights reserved. | Legal Information | Privacy Policy