



Search Results

Evaluate

- Advertisements
 - PDFReduce Insta ..
 - PDFTX6 10Gig UT ..
- Brochures
 - PDFTX6 10Gig UT ..
- FAQ's
- Performance Data
 - PDFETL UTP Chan ..
- Press Releases
- TG Terminati ..
- Termination ..
- Product Bulletins
 - PDFPANDUIT TG T ..
- White Papers
 - PDFTesting 10 G ..

Design a Solution

- Part Drawings
 - DXF-Mini-Com TX6 ..
 - PDFMini-Com TX6 ..
 - DWG-Mini-Com TX6 ..

How to Buy

- Bill of Material
- Favorite Products List
- Locate Distributor

Install & Maintain

- Installation Instructions
 - PDFTX6 10Gig UT ..

Home > Products Overview > Search Results >

Current refinements (click to remove) Search Tips Within Results

Text Search: 'CJ6X88TGBL-24'

Your search criteria matched only one product, shown below

CJ6X88TGBL-24



- Exceeds draft requirements of TIA/EIA-568-B.2-AD10 and ISO 11801 Class E_A Edition 2.1, and IEEE 802.3an-2006 ratified standard channel requirements for supporting 10GBASE^{-T}
- Each jack is 100% tested to ensure NEXT and RL performance and is individually serialized for traceability
- Utilizes patent-pending enhanced *Giga-TX*TMTechnology for jack terminations which optimizes performance by maintaining cable pair geometry and eliminating conductor untwist
- No punchdown tool required; termination tool (EGJT) ensures conductors are fully terminated by utilizing a smooth forward motion without impact on critical internal components for maximum reliability
- Optional termination tool (TGJT) reduces termination time by 25%, ideal for high volume installations
- Can be re-terminated a minimum of twenty times
- Blue termination cap designates *10Gig*TM Augmented Category 6 performance and provides a positive strain relief; helps control cable bend radius and securely retains wires

- Terminates 4 -pair, 22 – 26 AWG, 100 ohm, solid or stranded twisted pair cable
- Termination cap is color coded for T568A and T568B wiring schemes
- Accepts 6 and 8-position modular plugs without damage
- Can be clearly identified with optional labels and icons

Part Number	CJ6X88TGBL24
RoHS Compliancy Status	Compliant
Part Description	Category 6A, RJ45, 10 Gb/s, 8position, 8-wire universal module, bulk packaged.
Color	Black
No. of Module Spaces	1
Performance Level	Category 6A
Wiring Scheme	T568A/T568B
Min. Order UOM	PC
Min. Order Qty.	24
BOM Qty. (# of Pkgs.)	0
Add to Favorite Product List	

Please [register](#) to utilize the 'Bill of Materials', 'Submit Quotes' and 'Favorite Product List' features.