



Search Results

Evaluate

- FAQ's

How to Buy

- Bill of Material
- Favorite Products List
- Locate Distributor

Install & Maintain

- Installation Instructions
- PDF-TX5e Giga-TX ..

Home > Products Overview > Search Results >

Current refinements (click to remove) Search Tips € Within Results

Text Search: 'CJD5E88TOR'

Your search criteria matched only one product, shown below

CJD5E88TOR



- Exceeds TIA/EIA-568-B.2 Category 5e standard
- Shuttered door keeps out dust and debris when not in use
- Forward motion termination speeds installation and places no impact on critical internal components for maximum reliability
- No punchdown tool required, optional termination tool (CGJT) ensures conductors are fully terminated
- Utilizes patented *Giga-TX*[™] Technology to optimize performance by reducing conductor untwist to less than 1/8"
- Terminates 4 -pair 24 and 22 AWG 100 ohm solid unshielded twisted pair cable
- Can be re-terminated a minimum of 10 times
- Termination cap provides excellent strain relief, helps control cable bend radius and securely retains wires
- Termination cap includes universal label for T568A and T568B wiring schemes
- Accepts 6 and 8 position modular plugs without damage

- Red colored termination cap designates Category 5e performance with *Giga-TX*[™] Technology
- Can be clearly identified with optional labels and icons
- Compatible with *Mini-Com*[®] modular patch panels, faceplates and surface mount boxes

Part Number	CJD5E88TOR
RoHS Compliance Status	Compliant
Part Description	Category 5e, 8-position, 8-wire universal shuttered module.
Product Type	Copper Jack Module
Color	Orange
Modular Jack Type	RJ45
No. of Module Spaces	1
Performance Level	Category 5e
Pricing Description	MiniCom Shuttered Module, Cat 5e, UTP, Universal, Orange, T Style
Wiring Scheme	T568A/T568B
Min. Order UOM	PC
Min. Order Qty.	1
BOM Qty. (# of Pkgs.)	0
Add to Favorite Product List	€

Please [register](#) to utilize the 'Bill of Materials', 'Submit Quotes' and 'Favorite Product List' features.