

[support](#) | [locate distributor](#) | [about panduit](#) | [contact us](#)*World Leader in Network and Electrical Solutions*[HOME](#) | [SOLUTIONS](#) | [RESOURCES](#) | [PRODUCTS](#) | [SERVICES](#) | [LEARNING](#)SEARCH Current refinements (click ☒ to remove)☒ **Region** ▶ **USA** ☒ **Product Family** ▶ **Corrugated Loom Tubing – Slit** ☒ **Text Search:** 'CLT25N-10M630'**Your search criteria matched only one product, shown below.**

Corrugated Loom Tubing is offered for applications where spiral wrap or braided expandable sleeving may be difficult to install or where they do not offer the amount of protection required. T1 features a lengthwise slit which makes it easy to install onto a bundle of wires or a pre-assembled harness assembly.

- Protects and reduces the risk of damage to wiring
- Crush impact and abrasion resistant
- Slit wall design for ease of installation
- Hold in place with push type cable ties adhesive or push type mount
- Bundle wires in control panels

* Order number of reels required.
Contact Customer Service for additional sizes, materials, colors and bulk packaging.

Part Number: CLT25N-10M630

RoHS Compliancy Status: Compliant

Part Description: Slit Corrugated Loom Tubing is offered for applications where Spiral Wrap or Braided Expandable Sleeving may be difficult to install or they do not offer the amount of protection required.

Material: Heat Stabilized Nylon 6

Color: Black

Inside Diameter (In.): .27

Inside Diameter (mm): 6.7

Length Per Reel (ft.): 10,000

Length Per Reel (m): 3048

Outside Diameter (In.): .39

Outside Diameter (mm): 9.9mm

Temperature Range: -40°F to 230°F (-40°C to 110°C)

Min. Order UOM: RL

Min. Order Qty.: 1

BOM Qty. (# of Pkgs.)

Add to My Catalog

☐Please [register](#) to utilize the 'Bill of Materials', 'Submit Quotes' and 'My Catalog' features.[legal information](#) | [privacy policy](#) | [site map](#)

Copyright © 1995-2007, PANDUIT CORP. All rights reserved.