

Search Results

- Evaluate
- FAQ's
 - Product Bulletins
 - PDFObsolete and ..
 - Selection Guides
 - PDFConvenience ..
- How to Buy
- Bill of Material
 - Favorite Products List
 - Locate Distributor

Home > Products Overview > Search Results >

Current refinements (click  to remove) [Search Tips](#)

 Text Search: 'DNF10-250FIMB-E'

Your search criteria matched only one product, shown below

DNF10-250FIMB-E



- Disconnect can be inserted and removed from the male tab without the use of tools for lower installed cost
- Fully insulated design provides protection from electrical shorts
- Internal barrel serrations assure good wire contact and maximum tensile strength
- Internal wire stop assures proper length of insertion into terminal barrel, providing a higher quality connection
- Coupler, male, and female parts sold separately
- UL Flammability UL 94V -2/HB, maximum insulation temperature 221°F (105°C)
- UL and CSA rated up to 600 V per UL 310

▪ Part Number	DNF10250FIMBE
▪ RoHS Compliancy Status	Compliant
▪ Part Description	Male Disconnect, nylon fully insulated oversized housing, butted seam, 12- 10 AWG, .250 x .032 tab size.
▪ Product Type	Disconnects
▪ CSA Certified	Yes
▪ UL Listed	Yes
▪ Height (In.)	0.36
▪ Height (mm)	9.1
▪ Length (In.)	0.96
▪ Length (mm)	24.4
▪ Width (In.)	0.45
▪ Width (mm)	11.4
▪ CE Compliant	No
▪ Insulation	Nylon
▪ Max. Ins.	0.220
▪ Max. Ins. (mm)	5.6
▪ Panduit Color Code	Yellow
▪ Plating Type	Nickel
▪ Pricing Description	Terminal Convenience Package
▪ Tab Size (In.)	0.250 x 0.032
▪ Tab Size (mm)	6.3 x 0.8
▪ Temperature Rating	221 Degrees Fahrenheit (105 Degrees Celsius)
▪ Tool	CT-600-A†, CT-1550†, CT-1551†, CT-2500†
▪ Type	Male
▪ Wire Range	12 – 10 AWG
▪ Wire Range (mm²)	4.0 – 6.0
▪ Min. Order UOM	PC
▪ Min. Order Qty.	20
▪ BOM Qty. (# of Pkgs.)	0
▪ Add to Favorite Product List	

Please [register](#) to utilize the 'Bill of Materials', 'Submit Quotes' and 'Favorite Product List' features.