Search Results

Evaluate
- FAQ's

Design a Solution
- Catalog Cut Sheet
- PDF DNF18-110FIB..

How to Buy
- Bill of Material
- Favorite Products List
- Locate Distributor

Current refinements (click ☒ to remove) Search Tips

☒ **Text Search: 'DNF14206FIBX-L'**

Your search criteria matched only one product, shown below

DNF14206FIBX-L

- Disconnect can be inserted and removed from the male tab without the use of tools for lower installed cost
- Fully insulated design provides protection from electrical shorts
- Internal wire stop assures proper length of insertion into terminal barrel, providing a higher quality connection
- UL Flammability UL 94V -2/HB, maximum insulation temperature 221°F (105°C)
- UL and CSA rated up to 600 V per UL 310

Part Number	DNF14206FIBX-L
RoHS Compliancy Status	Compliant
Note	DNF14-206FIBX-L replaces DNF14206FIBX-C
Part Description	Female disconnect, (standard receptacle housings and expanded wire entry area for large wire insulation o.d.), nylon fully insulated, funnel entry, 16 – 14 AWG wire range and .187/.205 x .020 in. (4.8/5.2 x .5mm).
Product Type	Disconnects
Height (In.)	0.22
Height (mm)	5.6
Length (In.)	0.87
Length (mm)	22.1
Width (In.)	0.31
Width (mm)	7.9
CE Compliant	No
Insulation	Nylon
Max. Ins.	0.240
Max. Ins. (mm)	6.1
Panduit Color Code	Blue
Plating Type	Tinned
Pricing Description	Female Disconnect, nylon fully insulated, expanded entry, 16- 14 AWG, .187/.205 x .020 tab size, funnel entry
Tab Size (In.)	0.205/0.187 x 0.020
Tab Size (mm)	5.2/4.7 x 0.5
Temperature Rating	221 Degrees Fahrenheit (105 Degrees Celsius)
Tool	CT-100A
Wire Range	16 – 14 AWG
Wire Range (mm²)	1.5 – 2.5
Min. Order UOM	PC
Min. Order Qty.	50
BOM Qty. (# of Pkgs.)	0
Add to Favorite Product List	e

Please register to utilize the 'Bill of Materials', 'Submit Quotes' and 'Favorite Product List' features.

Copyright © 1995-2011, PANDUIT CORP. All rights reserved. | Legal Information | Privacy Policy