

Search Results

- Evaluate
- FAQ's
- Design a Solution
- Catalog Cut Sheet
 - PDFDNF18110FIB..
 - Part Drawings
 - PDFFemale Disco..
- How to Buy
- Bill of Material
 - Favorite Products List
 - Locate Distributor

Home > Products Overview > Search Results >

Current refinements (click  to remove) [Search Tips](#)

 Text Search: 'DNF14-250FI-L'

Your search criteria matched only one product, shown below

DNF14-250FI-L



- Disconnect can be inserted and removed from the male tab without the use of tools for lower installed cost
- Fully insulated design provides protection from electrical shorts
- Internal wire stop assures proper length of insertion into terminal barrel, providing a higher quality connection
- Barrel design with larger outside diameter for use with more common hand tools
- UL Flammability UL 94V -2/HB, maximum insulation temperature 221°F (105°C)
- UL and CSA rated up to 600 V per UL 310

Part Number	DNF14250FIL
RoHS Compliancy Status	Compliant
Note	DNF14250FIL replaces DNF14250FIC
Part Description	Female Disconnect, nylon fully insulated, metal sleeve, funnel entry, 16- 14 AWG, .250 x .032 tab size.
Product Type	Disconnects
CSA Certified	Yes
UL Listed	Yes
Height (In.)	0.24
Height (mm)	6.1
Length (In.)	0.94
Length (mm)	23.9
Width (In.)	0.36
Width (mm)	9.1
CE Compliant	No
Insulation	Nylon
Max. Ins.	0.160
Max. Ins. (mm)	4.1
Panduit Color Code	Blue
Plating Type	Tinned
Pricing Description	Female Disconnect, nylon fully insulated, metal sleeve, 16 14 AWG, .250 x .032 tab size, funnel entry
Tab Size (In.)	0.250 x 0.032
Tab Size (mm)	6.3 x 0.8
Temperature Rating	221 Degrees Fahrenheit (105 Degrees Celsius)
Tool	CT-100A, CT-600-A, CT-1550, CT-1551, CT-2500
Wire Range	16 – 14 AWG
Wire Range (mm ²)	1.5 – 2.5
Min. Order UOM	PC
Min. Order Qty.	50
BOM Qty. (# of Pkgs.)	0
Add to Favorite Product List	

Please [register](#) to utilize the 'Bill of Materials', 'Submit Quotes' and 'Favorite Product List' features.