



Search Results

- Evaluate
- FAQ's
- How to Buy
- Bill of Material
 - Favorite Products List
 - Locate Distributor

Home > Products Overview > Search Results >

Current refinements (click to remove) Search Tips

Text Search: 'DV14-187B-3K'

Your search criteria matched only one product, shown below

DV14-187B-3K



Vinyl barrel insulated funnel entry female disconnects. The barrel insulated designs allow for tight space applications where flashover at the receptacle end is not a concern. The PVC insulation forms an insulation crimp on the wire insulation. All polyvinylchloride 2 -piece insulated terminals are rated at 600 volts and designed for up to 105° C (221° F) operating temperature.

- Continuously molded design provides reliable, consistent performance through the applicator for a high quality termination every time
- Disconnect can be inserted and removed from the male tab without the use of tools for lower installed cost
- Metal insulation grip sleeve crimps to wire insulation, providing protection to the crimp joint during high vibration applications
- Internal barrel serrations assure good wire contact and maximum tensile strength
- Internal wire stop assures proper length of insertion into terminal barrel, providing a higher quality connection

- UL Flammability UL 94V -0, maximum insulation temperature 221°F (105°C)

Part Number	DV14-187B-3K
RoHS Compliancy Status	Compliant
Part Description	Female disconnect vinyl barrel insulated, funnel entry with plastic insulation crimp and internal wire stop. 16 – 14 AWG wire range, .187 x .032 in (4.8 x .8mm) tab size.
Product Type	Disconnects - Reel Fed
CSA Certified	Yes
UL Listed	Yes
Height (In.)	.10
Height (mm)	2.5
Length (In.)	.77
Length (mm)	19.6
Width (In.)	.23
Width (mm)	5.8
CA-800 Series Crimp Die	CD-800-2
CA9 Series Crimp Die	CD9-2A
CE Compliant	No
CE Marking	No
Max. Ins.	.170
Panduit Color Code	Blue
Pieces Per Reel	3000
Pricing Description	Female Disconnect, vinyl barrel insulated, 16- 14 AWG, .187 x .032 tab size, butted seam
Tab Size (In.)	.187 x .032
Tab Size (mm)	4.8 x .8
Wire Range	16 – 14 AWG
Wire Range (mm ²)	1.5 – 2.5
Min. Order UOM	PC
Min. Order Qty.	3000
BOM Qty. (# of Pkgs.)	0
Add to Favorite Product List	

Please [register](#) to utilize the 'Bill of Materials', 'Submit Quotes' and 'Favorite Product List' features.