Search Results

Evaluate
- FAQ's
- Product Bulletins
- PDF Obsolete and ..
- Selection Guides
- PDF Convenience ..

How to Buy
- Bill of Material
- Favorite Products List
- Locate Distributor

Current refinements (click ☒ to remove) Search Tips

☒ **Text Search: 'DV18-250B-E'**

Your search criteria matched only one product, shown below

DV18-250B-E

• Disconnect can be inserted and removed from the male tab without the use of tools for lower installed cost
• Internal barrel serrations assure good wire contact and maximum tensile strength
• Internal wire stop assures proper length of insertion into terminal barrel, providing a higher quality connection
• UL Flammability UL 94V -0, maximum insulation temperature 221°F (105°C)
• UL and CSA rated up to 600 V per UL 310, where applicable
‡UL and CSA approved tooling/product combinations.
CSA approved tooling/product combinations.

Part Number	DV18-250B-E
RoHS Compliancy Status	Compliant
Part Description	Female Disconnect, vinyl barrel insulated, butted seam, 22- 18 AWG, .250 x .032 tab size.
Product Type	Disconnects
CSA Certified	Yes
UL Listed	Yes
Height (In.)	0.12
Height (mm)	3.0
Length (In.)	0.81
Length (mm)	20.6
Width (In.)	0.29
Width (mm)	7.4
CE Compliant	No
Insulation	Vinyl
Max. Ins.	0.150
Max. Ins. (mm)	3.8
Panduit Color Code	Red
Plating Type	Tinned
Pricing Description	Terminal Convenience Package
Tab Size (In.)	0.250 x 0.032
Tab Size (mm)	6.3 x 0.8
Temperature Rating	221 Degrees Fahrenheit (105 Degrees Celsius)
Tool	CT-1525‡, CT-2500‡
Wire Range	22 – 18 AWG
Wire Range (mm²)	0.5 – 1.0
Min. Order UOM	PC
Min. Order Qty.	20
BOM Qty. (# of Pkgs.)	0
Add to Favorite Product List	

Please register to utilize the 'Bill of Materials', 'Submit Quotes' and 'Favorite Product List' features.

Copyright © 1995-2011, PANDUIT CORP. All rights reserved. | Legal Information | Privacy Policy