



Search Results

- Evaluate
- FAQ's
- How to Buy
- Bill of Material
- Favorite Products List
- Locate Distributor

[Home](#) > [Products Overview](#) > [Search Results](#) >

Current refinements (click to remove) [Search Tips](#) Within Results

Text Search: 'F5D3-4M3Y'

Your search criteria matched only one product, shown below

F5D3-4M3Y



- Pass all TIA/EIA-568-B.3 performance requirements
- Insertion loss per connection: 0.10dB typical; 0.30dB maximum
- Factory terminated and 100% tested for insertion loss
- Insertion loss data recorded for every multimode patch cord
- Lifetime traceability of test data to a Q.C. number on each patch cord
- SC Duplex Patch Cords include SC Duplex Clips to maintain polarity
- Highest quality flame retardant fiber optic cable with tight -buffered coating on each optical fiber

Part Number	F5D3-4M3Y
RoHS Compliancy Status	Intended for use in fixed installations which are outside the scope of RoHS
Note	F5D3-4M3Y replaces F5D3-4M3
Part Description	SC to FC multimode duplex patch cord (two SC connectors on one end and two FC connectors on the other end) - 50/125 μ m.
Product Type	Hybrid Patch Cords
Length (m)	3
Fiber Compatibility	50/125 μ m
Fiber Cable Size	3mm
Fiber Cable Type	Jacketed
Fiber Type	Multimode
Connector 1 Type	SC Connector
Connector 2 Type	FC Connector
End Configurations	SC to FC
Fiber Count	2
Flammability Rating	Riser (OFNR)
Pricing Description	PC SC To FC 50 μ m Dupl 3m
Min. Order UOM	PC
Min. Order Qty.	1
BOM Qty. (# of Pkgs.)	0
Add to Favorite Product List	

Please [register](#) to utilize the 'Bill of Materials', 'Submit Quotes' and 'Favorite Product List' features.