Search Results

Evaluate
- FAQ's
Design a Solution
- Catalog Cut Sheet
- PDF HST0.4-3-Q2Y
- Part Drawings
- PDF Thick Wall P..
- Specification Sheets
- PDF Thick Wall P..
How to Buy
- Bill of Material
- Favorite Products List
- Locate Distributor

Home > Products Overview > Search Results >

Current refinements (click ☒ to remove) Search Tips

☒ **Text Search: 'HST0.8-9-X2Y'**

**Your search criteria matched only one product, shown below**

## HST0.8-9-X2Y

• Shrink ratio of 3:1 insulates a wide range of diameters and irregular shapes, which reduces inventory costs
• Cross -linked, UV resistant material improves flame retardancy, chemical, and temperature resistance
• Thick wall product seals and insulates in one step to speed installation
• Meets Mil Spec AMS-DTL-23053/15 Class 1
* For red, add 2 to end of part number package suffix (Example HST0.4 -3-Q2).

| | |
|---|---|
| Part Number | HST0.8-9-X2Y |
| RoHS Compliancy Status | Compliant |
| Note | HST0.8-9-X2Y replaces HST0.8-9-X2 |
| Part Description | Thick Wall Heat Shrink provides excellent protection above or below ground level and is suitable for wet locations and direct burial (UL486D) |
| Material | Highly flame retardant adhesive lined cross-linked polyolefin |
| Color | Red |
| CSA Certified | Yes |
| Military Specification | AMS-DTL-23053/15 Class 1 |
| UL Listed | Yes |
| UL Recognized | No |
| Length (In.) | 9.0 |
| Length (mm) | 228.6 |
| Copper Conductor Size Range | #8 AWG – #1/0 |
| CE Compliant | No |
| Conductor Size Range (mm) | 10 – 50 |
| Flammability Rating | Flame Retardant |
| Max. Connector O.D. (In.) | 0.650 |
| Max. Connector O.D. (mm) | 16.5 |
| Max. Recovered I.D. (In.) | 0.22 |
| Max. Recovered I.D. (mm) | 5.6 |
| Min. Cable O.D. (In.) | 0.240 |
| Min. Cable O.D. (mm) | 6.1 |
| Min. Expanded I.D. (In.) | 0.75 |
| Min. Expanded I.D. (mm) | 19.1 |
| Nominal Recovered Wall Thickness (In.) | 0.09 |
| Nominal Recovered Wall Thickness (mm) | 2.3 |
| Pricing Description | Heat Shrink Thick Adhesive, .8"(20.3mm) Dia, Red |
| Shrink Ratio | 3:1 |
| Temperature Range | -67°F – 230°F (-55°C – 110°C) |
| Type | WET-SHRINK Thick Wall Heat Shrink Adhesive |
| Min. Order UOM | PC |
| Min. Order Qty. | 10 |
| BOM Qty. (# of Pkgs.) | 0 |
| Add to Favorite Product List | |

**Please register to utilize the 'Bill of Materials', 'Submit Quotes' and 'Favorite Product List' features.**


Copyright © 1995-2011, PANDUIT CORP. All rights reserved. | Legal Information | Privacy Policy