Search Results

Evaluate
- FAQ's
Design a Solution
- Catalog Cut Sheet
- PDF HST0.4-3-Q2Y
- Part Drawings
- PDF Thick Wall P..
- Specification Sheets
- PDF Thick Wall P..
How to Buy
- Bill of Material
- Favorite Products List
- Locate Distributor

Home > Products Overview > Search Results >

Current refinements (click ☒ to remove) Search Tips

☒ **Text Search: 'HST1.1-6-X2Y'**

Your search criteria matched only one product, shown below

HST1.1-6-X2Y

- Shrink ratio of 3:1 insulates a wide range of diameters and irregular shapes, which reduces inventory costs
- Cross -linked, UV resistant material improves flame retardancy, chemical, and temperature resistance
- Thick wall product seals and insulates in one step to speed installation
- Meets Mil Spec AMS-DTL-23053/15 Class 1

* For red, add 2 to end of part number package suffix (Example HST0.4 -3-Q2).

Part Number	HST1.1-6-X2Y
RoHS Compliancy Status	Compliant
Note	HST1.1-6-X2Y replaces HST1.1-6-X2
Part Description	Thick Wall Heat Shrink provides excellent protection above or below ground level and is suitable for wet locations and direct burial (UL486D)
Material	Highly flame retardant adhesive lined cross-linked polyolefin
Color	Red
CSA Certified	Yes
Military Specification	AMS-DTL-23053/15 Class 1
UL Listed	Yes
UL Recognized	No
Length (In.)	6.0
Length (mm)	152.4
Copper Conductor Size Range	#2 AWG – #4/0
CE Compliant	No
Conductor Size Range (mm)	35 – 95
Flammability Rating	Flame Retardant
Max. Connector O.D. (In.)	0.875
Max. Connector O.D. (mm)	22.2
Max. Recovered I.D. (In.)	0.38
Max. Recovered I.D. (mm)	9.5
Min. Cable O.D. (In.)	0.400
Min. Cable O.D. (mm)	10.1
Min. Expanded I.D. (In.)	1.10
Min. Expanded I.D. (mm)	27.9
Nominal Recovered Wall Thickness (In.)	0.12
Nominal Recovered Wall Thickness (mm)	3.0
Pricing Description	Heat Shrink Thick Adhesive, 1.1"(27.9mm) Dia, Red
Shrink Ratio	3:1
Temperature Range	-67°F – 230°F (-55°C – 110°C)
Type	WET-SHRINK Thick Wall Heat Shrink Adhesive
Min. Order UOM	PC
Min. Order Qty.	10
BOM Qty. (# of Pkgs.)	0
Add to Favorite Product List	e

Please register to utilize the 'Bill of Materials', 'Submit Quotes' and 'Favorite Product List' features.

Copyright © 1995-2011, PANDUIT CORP. All rights reserved. | Legal Information | Privacy Policy