



Search Results

- Evaluate
- FAQ's
- How to Buy
- Bill of Material
  - Favorite Products List
  - Locate Distributor

Home > Products Overview > Search Results >

Current refinements (click to remove)    Search Tips

Text Search: 'HSTT06-48-Q4'

Your search criteria matched only one product, shown below

HSTT06-48-Q4



- Shrink ratio of 2:1 insulates a wide range of diameters and irregular shapes
  - Cross -linked, UV resistant material improves flame retardancy, chemical, and temperature resistance
- For clear, add "C" to end of part number package suffix (Example HSTT05 -48-QC). Contact customer service for additional color information.

Meets Mil Spec AMSDTL-23053/5 Class 1(Colors), Class 2 (Clear)

|  |                                        |                                                      |
|--|----------------------------------------|------------------------------------------------------|
|  | Part Number                            | HSTT0648-Q4                                          |
|  | RoHS Compliance Status                 | Compliant                                            |
|  | Part Description                       | Thin Wall Polyolefin Heat Shrink                     |
|  | Material                               | Flame retardant polyolefin cross-linked except clear |
|  | Color                                  | Yellow                                               |
|  | CSA Certified                          | Yes                                                  |
|  | Military Specification                 | AMS-DTL-23053/5 Class 1                              |
|  | UL Recognized                          | E122770                                              |
|  | Length (ft.)                           | 4                                                    |
|  | Length (m)                             | 1.2                                                  |
|  | CE Compliant                           | No                                                   |
|  | CE Marking                             | No                                                   |
|  | Flammability Rating                    | Flame Retardant                                      |
|  | Max. Recovered I.D. (In.)              | .031                                                 |
|  | Max. Recovered I.D. (mm)               | .8                                                   |
|  | Min. Expanded I.D. (In.)               | .063                                                 |
|  | Min. Expanded I.D. (mm)                | 1.6                                                  |
|  | Nominal Diameter / Size                | .063                                                 |
|  | Nominal Recovered Wall Thickness (In.) | .017                                                 |
|  | Nominal Recovered Wall Thickness (mm)  | .4                                                   |
|  | Pricing Description                    | Heat Shrink Thin, .06"(1.6mm) Dia, Yellow            |
|  | Shrink Ratio                           | 2:1                                                  |
|  | Temperature Range                      | -67°F to 275°F (-55°C to 135°C)                      |
|  | Min. Order UOM                         | PC                                                   |
|  | Min. Order Qty.                        | 25                                                   |
|  | BOM Qty. (# of Pkgs.)                  | <input type="text" value="0"/>                       |
|  | Add to Favorite Product List           |                                                      |

Please [register](#) to utilize the 'Bill of Materials', 'Submit Quotes' and 'Favorite Product List' features.