



Products

- Products Overview
- Product Search
- Evaluate
 - FAQ's
- How to Buy
 - Bill of Material
 - Favorite Products List
 - Locate Distributor

Home > Products Overview > Product Search >

Current refinements (click to remove) Search Tips

Part Number > HSTT09-48-Q2

Your search criteria matched only one product, shown below

HSTT09-48-Q2



- Shrink ratio of 2:1 insulates a wide range of diameters and irregular shapes
- Cross -linked, UV resistant material improves flame retardancy, chemical, and temperature resistance

For clear, add "C" to end of part number package suffix (Example HSTT05-48-QC). Contact customer service for additional color information.

Meets Mil Spec AMS-DTL-23053/5 Class 1(Colors), Class 2 (Clear)

Part Number	HSTT0948-Q2
RoHS ComplianceStatus	Compliant
Part Description	Thin Wall Polyolefin HeaShrink
Material	Flame retardantpolyolefin cross-linked except clear
Color	Red
CSA Certified	Yes
Military Specification	AMS-DTL-23053/5 Class 1
UL Recognized	E122770
Length (ft.)	4
Length (m)	1.2
CE Compliant	No
CE Marking	No
FlammabilityRating	Flame Retardant
Max. Recovered I.D. (In.)	.046
Max. Recovered I.D. (mm)	1.2
Min. Expanded I.D(In.)	.093
Min. Expanded I.D(mm)	2.4
Nominal Diameter Size	.093
Nominal RecoveredWall Thickness (In.)	.020
Nominal RecoveredWall Thickness (mm)	.5
Pricing Description	Heat Shrink Thin,.09"(2.4mm) Dia, Red
Shrink Ratio	2:1
TemperatureRange	-67°F to 275°F (55°C to 135°C)
Min. OrderUOM	PC
Min. OrderQty.	25
BOM Qty. (# ofPkgs.)	0
Add to Favorite Product List	

Please [register](#) to utilize the 'Bill of Materials', 'Submit Quotes' and 'Favorite Product List' features.