



Search Results

- Evaluate
- FAQ's
- How to Buy
- Bill of Material
  - Favorite Products List
  - Locate Distributor

Home > Products Overview > Search Results >

Current refinements (click to remove)    Search Tips

**Text Search: 'HSTT09-M2'**

Your search criteria matched only one product, shown below

HSTT09-M2



Flexible Ployolefin DRY-SHRINK<sup>TM</sup>Heat Shrink Tubing

- General Purpose heat shrink tubing for dry locations
- Applications include insulating, protecting, harnessing and identifying wires.
- Material Type: Crosslinked Polyolefin
- Shrink Ratio: 2:1
- Temperature Range: -67°F to 275°F (-55°C to 135°C)
- Flammability Rating: Flame retardant EXCEPT clear
- Voltage: 600 V
- UL Recognized, CSA Certified
- Mil Spec: AMSDTL-23053/5 Class 1 (Colors) Class 2 (Clear)

|                                        |                                        |
|----------------------------------------|----------------------------------------|
| Part Number                            | HSTT09M2                               |
| RoHS Compliance Status                 | Compliant                              |
| Part Description                       | Thin Wall Polyolefin Heat Shrink       |
| Material                               | Polyolefin cross-linked                |
| Color                                  | Red                                    |
| CSA Certified                          | Yes                                    |
| Military Specification                 | AMS-DTL-23053/5 Class 1                |
| UL Recognized                          | E122770                                |
| CE Compliant                           | No                                     |
| CE Marking                             | No                                     |
| Flammability Rating                    | Flame Retardant                        |
| Length Per Reel (ft.)                  | 1000                                   |
| Length Per Reel (m)                    | 304.8                                  |
| Max. Recovered I.D. (In.)              | .046                                   |
| Max. Recovered I.D. (mm)               | 1.2                                    |
| Min. Expanded I.D. (In.)               | .093                                   |
| Min. Expanded I.D. (mm)                | 2.4                                    |
| Nominal Diameter / Size                | .093                                   |
| Nominal Recovered Wall Thickness (In.) | .020                                   |
| Nominal Recovered Wall Thickness (mm)  | .5                                     |
| Pricing Description                    | Heat Shrink Thin, .09"(2.4mm) Dia, Red |
| Shrink Ratio                           | 2:1                                    |
| Temperature Range                      | -67°F to 275°F (55°C to 135°C)         |
| Min. Order UOM                         | RL                                     |
| Min. Order Qty.                        | 1                                      |
| BOM Qty. (# of Pkgs.)                  | <input type="text" value="0"/>         |
| Add to Favorite Product List           |                                        |

Please [register](#) to utilize the 'Bill of Materials', 'Submit Quotes' and 'Favorite Product List' features.