

Search Results

- Evaluate
- FAQ's
- How to Buy
- Bill of Material
 - Favorite Products List
 - Locate Distributor

Home > Products Overview > Search Results >

Current refinements (click  to remove) Search Tips

 Text Search: 'HSTT100-48-5-2'

Your search criteria matched only one product, shown below

HSTT100-48-5-2



- Shrink ratio of 2:1 insulates a wide range of diameters and irregular shapes
 - Cross -linked, UV resistant material improves flame retardancy, chemical, and temperature resistance
- For clear, add "C" to end of part number package suffix (Example HSTT05-48-QC). Contact customer service for additional color information.

Meets Mil Spec AMS-DTL-23053/5 Class 1(Colors), Class 2 (Clear)

 Part Number	HSTT10048-5-2
 RoHS CompliancyStatus	Compliant
 Part Description	Thin Wall Polyolefin HeaShrink
 Material	Flame retardantpolyolefin cross-linked except clear
 Color	Red
 CSA Certified	Yes
 Military Specification	AMS-DTL-23053/5 Class 1
 UL Recognized	E122770
 Length (ft.)	4
 Length (m)	1.2
 CE Compliant	No
 CE Marking	No
 FlammabilityRating	Flame Retardant
 Max. Recovered I.D. (In.)	.500
 Max. Recovered I.D. (mm)	12.7
 Min. Expanded I.D(In.)	1.00
 Min. Expanded I.D(mm)	25.4
 Nominal Diameter Size	1.00
 Nominal RecoveredWall Thickness (In.)	.035
 Nominal RecoveredWall Thickness (mm)	.9
 Pricing Description	Heat Shrink Thin,1"(25.4mm) Dia, Red
 Shrink Ratio	2:1
 Temperature Range	-67°F to 275°F (55°C to 135°C)
 Min. OrderUOM	PC
 Min. OrderQty.	5
 BOM Qty. (# ofPkgs.)	0
 Add to Favorite Product List	

Please [register](#) to utilize the 'Bill of Materials', 'Submit Quotes' and 'Favorite Product List' features.