



Search Results

- Evaluate
- FAQ's
- How to Buy
- Bill of Material
  - Favorite Products List
  - Locate Distributor

Home > Products Overview > Search Results >

Current refinements (click to remove)    [Search Tips](#)

**Text Search: 'HSTT12-M2'**

Your search criteria matched only one product, shown below

HSTT12-M2



- Flexible Ployolefin DRY-SHRINK<sup>TM</sup>Heat Shrink Tubing
- General Purpose heat shrink tubing for dry locations
  - Applications include insulating, protecting, harnessing and identifying wires.
  - Material Type: Crosslinked Polyolefin
  - Shrink Ratio: 2:1
  - Temperature Range: -67°F to 275°F (-55°C to 135°C)
  - Flammability Rating: Flame retardant EXCEPT clear
  - Voltage: 600 V
  - UL Recognized, CSA Certified
  - Mil Spec: AMSDTL-23053/5 Class 1 (Colors) Class 2 (Clear)

|  |                                        |                                        |
|--|----------------------------------------|----------------------------------------|
|  | Part Number                            | HSTT12M2                               |
|  | RoHS Compliance Status                 | Compliant                              |
|  | Part Description                       | Thin Wall Polyolefin Heat Shrink       |
|  | Material                               | Polyolefin cross-linked                |
|  | Color                                  | Red                                    |
|  | CSA Certified                          | Yes                                    |
|  | Military Specification                 | AMS-DTL-23053/5 Class 1                |
|  | UL Recognized                          | E122770                                |
|  | CE Compliant                           | No                                     |
|  | CE Marking                             | No                                     |
|  | Flammability Rating                    | Flame Retardant                        |
|  | Length Per Reel (ft.)                  | 1000                                   |
|  | Length Per Reel (m)                    | 304.8                                  |
|  | Max. Recovered I.D. (In.)              | .062                                   |
|  | Max. Recovered I.D. (mm)               | 1.6                                    |
|  | Min. Expanded I.D. (In.)               | .125                                   |
|  | Min. Expanded I.D. (mm)                | 3.2                                    |
|  | Nominal Diameter / Size                | .125                                   |
|  | Nominal Recovered Wall Thickness (In.) | .020                                   |
|  | Nominal Recovered Wall Thickness (mm)  | .5                                     |
|  | Pricing Description                    | Heat Shrink Thin, .12"(3.2mm) Dia, Red |
|  | Shrink Ratio                           | 2:1                                    |
|  | Temperature Range                      | -67°F to 275°F (55°C to 135°C)         |
|  | Min. Order UOM                         | RL                                     |
|  | Min. Order Qty.                        | 1                                      |
|  | BOM Qty. (# of Pkgs.)                  | <input type="text" value="0"/>         |
|  | Add to Favorite Product List           |                                        |

Please [register](#) to utilize the 'Bill of Materials', 'Submit Quotes' and 'Favorite Product List' features.